










HPL07057EN

	Color	Part no. Article no.	Price See price list	Std. pack	Notes	Information relevant for export to North America 
Neutral terminal						
For connecting a 5th conductor in enclosure E-PKZ2, E54-PKZ2						
	–	–	N-PKZ2 003219	1 off	–	
Door coupling handles						
Degree of protection IP65 / UL/CSA Type 4X/Type 12						
	For use as main switch to EN 60204	Black	PKZ2-XH 106127	1 off 	Lockable in 0-position Suitable for 3 padlocks with 4 – 8 mm hasp thickness	Product Standards UL 508; CSA-C22.2 No. 14; IEC60947-4-1; CE marking E36332 UL File No. NLRV UL CCN 12528 CSA File No. 3211-05 NA Certification UL Listed, CSA certified
	For use in MCC distribution boards with PKZ2 turned through 90°. For use as main switch according to EN 60204	Black	PKZ2-XH-MCC 106130	1 off 		
	For use as a main switch with emergency switching off function to EN 60204	Red-yellow	PKZ2-XRH 106128	1 off 		
Plug-in extension shaft for door coupling handle						
Can be cut to any required length for mounting depths from 171 – 300 mm						
	–	–	PKZ2-XAH 106129	1 off 	–	Product Standards UL 508; CSA-C22.2 No. 14; IEC60947-4-1; CE marking E36332 UL File No. NLRV UL CCN 12528 CSA File No. 3211-05 NA Certification UL Listed, CSA certified
Rotary handle for insulated enclosures CI19(23)...-PKZ2						
	–	Black	PKZ2-XH-CI 138580	1 off	–	
	–	Red-yellow	PKZ2-XRH-CI 138581	1 off	–	

