

Power-Return Steel Rules – High-Visibility Case



928-25HV

- Same as No. 922 series, but with high-visibility case.
- High-visibility, high-impact orange case makes it easy to find in a tool box, pouch, and on the jobsite.
- 16" (406 mm) and 19.2" (485 mm) stud-center marks.
- Tape measure holders available.

Cat. No.	Blade Length	Width	Weight (lbs.)
928-16HV	16' (5 m)	3/4" (19 mm)	.45
928-25HV	25' (7.5 m)	1" (25 mm)	1.00

Fiberglass Tapes

Woven Fiberglass Tape – Case

- Woven fiberglass tape with moisture-proof coating of polyvinyl chloride assures durability and protects against oil or chemicals.
- Can be immersed in water without adverse effects.
- All metal parts are nickel-plated for protection against rust.
- End-hooks are permanently attached to reinforced strip.
- Black case and reel are ruggedly built, yet lightweight and comfortable to use.
- Tape line graduated in feet and inches to 8ths.
- Black graduating numbers and red foot markings on yellow background.
- Protective carrying case encloses tape completely.
- Tape ring tucks neatly into case opening for storage.



946-100

Cat. No.	Length	Width	Weight (lbs.)
946-50	50' (15 m)	1/2" (13 mm)	.80
946-100	100' (30 m)	1/2" (13 mm)	1.20

Woven Fiberglass Tape – Open-Reel

- Woven fiberglass tape with moisture-proof coating of polyvinyl chloride assures durability and protects against oil or chemicals.
- Can be immersed in water without adverse effects.
- Black figures on a yellow background are easy to read.
- All metal parts are nickel-plated for protection against rust.
- End hooks are permanently attached to a reinforced strip.
- Case and reel are ruggedly built, yet lightweight and comfortable to use.
- Tape line is graduated in feet and inches to 8ths.
- Graduations and numbers are black; foot markings are red.
- Contained in a high-visibility orange open reel and is easy to handle and rewind.
- Line will not collect dirt or bring debris into the case.



946-150

Cat. No.	Length	Width	Weight (lbs.)
946-150	150' (46 m)	1/2" (13 mm)	1.70

All dimensions are in inches and (millimeters) unless otherwise specified.

▲WARNING: Always wear approved eye protection.

▲WARNING: Do NOT open case. Spring motor is under tension, and opening case may cause injury.

▲WARNING: Never use on or near live electrical circuits.

▲CAUTION: To prevent high speed rewinding, apply slight pressure with forefinger on the underside of the blade.

