



Dimensions in Inches (mm)

Plugs

| Description | Cord Diameter | Catalog Number | |
|--|---------------------------|-------------------|-------------------|
| Insulgrip® Plug, black and white nylon. | .230"-.720" (5.8-18.3) | HBL5666C | HBL5466C |
| Insulgrip® Plug, corrosion resistant, yellow nylon. | .230"-.720" (5.8-18.3) | HBL56CM66C | HBL54CM66C |
| 8-Position Insulgrip® Angle Plug, black and white nylon. | .325"-.655" (8.3-16.6) | HBL5666CA | HBL5466CA |
| Valise® Plug, yellow nylon. | .220"-.660" (5.6-16.8) | HBL5666VY | HBL5464VY |

Note: See page A-47 for accessories.



15A 250V
 NEMA 6-15P
 UL CSA
 1.5 HP



20A 250V
 NEMA 6-20P
 UL CSA
 2 HP

Insulgrip® Flanged Inlets

| Description | Catalog Number | |
|---------------------------|-----------------|-----------------|
| Nylon casing, back wired. | HBL5678C | HBL5478C |

Note: Flanged inlets are not HP rated.
 See page A-47 for accessories.



15A 250V
 NEMA 6-15P
 UL CSA



20A 250V
 NEMA 6-20P
 UL CSA

For quick visual identification of circuits or configurations.

Colored Cord Clamps*

| Description | Color | Catalog Number |
|--|--------|-----------------------|
| For use with 15A and 20A, 2 pole/3 wire, insulgrip plugs and connectors with cord diameter range of .230"-.720" (5.8-18.3) only. | Blue | HBLCORDCLAMPBL |
| | Green | HBLCORDCLAMPGN |
| | Orange | HBLCORDCLAMPOR |
| | Purple | HBLCORDCLAMPP |
| | Red | HBLCORDCLAMPR |
| | Yellow | HBLCORDCLAMPY |

Note: *Clamp only. Contains no screws. Order in increments of 10. Not UL Listed or CSA Certified.