

SIRIUS 3SE5, 3SE2 mechanical safety switches

Hinge switches

3SE2, plastic enclosures with integrated hinge

Selection and ordering data

3 contacts · Degree of protection IP65 · Cable entry 2 × (M20 × 1.5)

Version	Slow-action contacts	DT	Complete units <input type="checkbox"/>
			Article No.

Plastic enclosures with integrated hinge



3SE2283

With integrated hinge

(Delivery includes additional hinge and fixing accessories)

• Aluminum hinge					
- Operating angle 4°	1 NO + 2 NC	↻ A		3SE2283-0GA43	
- Operating angle 4°	3 NC	↻ B		3SE2283-6GA43	
- Operating angle 8°	1 NO + 2 NC	↻ C		3SE2283-0GA53	
- Operating angle 8°	3 NC	↻ C		3SE2283-6GA53	
• High-grade steel hinge					
- Operating angle 4°	1 NO + 2 NC	↻ B		3SE2283-0GA44	
- Operating angle 4°	3 NC	↻ C		3SE2283-6GA44	

↻ Positive opening according to IEC 60947-5-1, Appendix K.

Accessories/spare parts

Version	DT	Article No.
---------	----	-------------

Accessories



3SX3225

Additional hinge

(delivered with fixing accessories)

• Made of aluminum	↻ D	3SX3225
• Made of high-grade steel	↻ D	3SX3231