

PAN-WAY[™] Power Rated Junction Boxes

PAN-WAY Power Rated Junction Boxes are used in surface mounted power or network cabling applications.

Junction Box Benefits:

- UL-5A Listed to 600V and CSA 22.2 No. 62.93 Listed to 300V
- Optimized for use with any standard NEMA faceplate, including *MINI-COM*[®] Designer or Executive Series faceplates
- Pre-scored breakouts on sides for raceway entry

Standard Colors:



Colors shown are approximate.



	breakouts in the bottom
• (Compatible with LD profile
I	raceways, PD profile raceway

Conduit and rectangular

raceways, PD profile raceways and T3 (Transition fitting) (See page N9)



See **pg. J13** for raceway <u>compatibility</u> guide

Power to 600V

Part Number	Description	Color	Std. Pkg. Qty.	Std. Ctn. Qty.
ower Rated Si JBP1IW JBP1WH JBP1EI JBP1IG JBP1BR JBP1BL	Single Gang Box L= 5.05" W= 3.31" H= 1.75" (128.3mm)(84.1mm)(44.5mm) Conduit breakouts: 1", ¾", ½"	Off White White Elec. Ivory Lt. Gray Brown Black	1 pc.	10 pcs.

For use with all single channel

raceways (See page J13 for compatibility)



Power Rated Single Gang "Deep" Style Box

JBP1DIWSingle Gang "Deep" Style box—base a cover.JBP1DEIL= 5.05" W= 3.31" H= 2.75"JBP1DIG(131.8mm) (131.8mm) (69.9mm)JBP1DBRConduit breakouts: 1", ¾", ½"	and Off White White Elec. Ivory Lt. Gray Brown Black	10 pcs.
--	---	---------

• For use with all single channel raceways (See **page J13** for compatibility)

Power Rated Double Gang Box

	JBP2IW JBP2WH JBP2EI JBP2IG JBP2BR JBP2BL	Double Gang Box—base & cover (screws included) L= 5.05" W= 5.05" H= 1.62" (128.3mm) (128.3mm) (41.1mm) Conduit breakouts: ¾", ½"	Off White White Elec. Ivory Lt. Gray Brown Black	1 pc.	10 pcs.
--	--	--	---	-------	---------

ORDERING INFORMATION:

Order number of pieces required, in multiples of Standard Package Quantity.

• For use with all single channel raceways (See page J13 for compatibility)

See Double Gang Faceplates pg. J3-J4

J1

JUNCTION BOXES