

# STZW402 | KI™ Z-WAVE

ELECTRONIC THERMOSTAT FOR SMART HOME

4000 W



## CONNECTED COMFORT

KI Z-Wave thermostats can easily be integrated into your home's Z-Wave network, so you can adjust the temperature setpoint of rooms in your home from a distance.



**INTEGRATES EASILY  
WITH A SMART HOME HUB**



**CONTROL WITH  
A MOBILE APPLICATION  
DEPENDING ON THE HUB**



**ELECTRICITY SAVINGS**  
ENERGY SAVINGS OF 10-15%  
DEPENDING ON USE\*

### COMPATIBILITY

- Z-Wave hub required
- Z-Wave Plus certified

### COLOUR

- white

### FINISH

- molded plastic

### WATTAGE AND VOLTAGE

- 150 W to 2000 W @ 120 V
- 300 W to 4000 W @ 240 V

### CONTROL

- two functions available: comfort and economy
- two- or four-wire connection
- outdoor temperature display†
- frost-free warning
- display in Celsius or Fahrenheit
- backlit screen with adjustable intensity

### ACCURACY

- accurate ambient temperature control of  $\pm 0.5$  °C (1 °F)
- CSA C828-13
- temperature sensing with thermistor

### TEMPERATURE RANGE

- 5 to 30 °C (41 to 86 °F)

### WARRANTY

- three years

\* independent study

† depending on the central controller and its application

COMPATIBLE WITH



WORKS WITH  
**SmartThings**

FOR HOME AUTOMATED SYSTEM COMPATIBILITIES AND INSTRUCTIONS ON CONNECTING TO YOUR KI THERMOSTAT, VISIT [WWW.STELPRO.COM](http://WWW.STELPRO.COM).

## TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	PACKAGING	UNIT PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ		
STZW402WB+	150/300	2000/4000	120/240	16.7	50/60	BOX	96.00

Dimensions: 4 7/8 in. (124 mm) wide, 4 7/8 in. (124 mm) high and 1 3/8 in. (29 mm) deep

# °STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at [www.stelpro.com](http://www.stelpro.com).



FC\_STZW402\_EN\_280420

