

YDS25

by Burndy
Catalog ID: YDS25

Prop 65 Notice

Copper Hysplice Tension, 1/0 Str., 7-1/4 in L, Full Tension Sleeve for All Aluminum Compressed and Compact Conductors.

Features: Made Of Pure Copper Tubing, Designed To Develop The Full Rated Breaking Strength Of Hard Drawn Or Medium Hard Drawn Copper Conductor, Installed With Standard Tooling, Die Index: 165 Element A, Conductor Type: Stranded Copper, Tools, Die Set Catalog Number, And (number Of Crimps): MD7, MD6 Tool, W165 Die, (6), Y35, Y750 Tool, U165/U205 Die, (6), Y45 Tool, U Die With Adapter PT-6515, Y46 Tool, U Die With Adapter PUADP-1



Product Details

General

Application	For Stranded Copper Conductors
Connector Type	Splice
Die Index	165
Material	Copper
Oxide Inhibitor Type	Penetrox E
Physical Attribute - Number of Crimps Required	6
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YDS
UPC	781810564820

Dimensions

Dimension - B Length fraction	2-3/5 in
Dimension - B Length inch	2.59 in
Dimension - L Length Overall mm	137 mm
Dimension - Length Overall inch	5.38 in
Dimension - Outside Diameter inch	0.63 in

Conductor Related

Conductor - Copper Str Size	1/0 AWG
-----------------------------	---------

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No

Certification - cULus	No
Industry Standard(s)	RUS
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	25
-----------------------	----

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)