

**MULTI-BASE BI-PIN HALOGEN LAMPHOLDERS**

**IS128-12SEW GX5.3 Base Offset Screw Mount Lampholder**

		<p><b>5.3 MM PIN SPACING</b></p>	<ul style="list-style-type: none"> <li>- Rectangular porcelain body</li> <li>- Copper, nickel-plated double wipe contacts with stainless steel reinforcing springs</li> <li>- Standard lead wires are 18 AWG SEW-1 (SF1) 200°C, 12" long, stripped 1/2"</li> <li>- Offset holes on 2 corners of socket for fast and easy mounting</li> <li>- Wire exit from back of socket</li> <li>- Rated 8A 24V</li> <li>- cURus Recognized</li> </ul>
<p>MR16</p>	<p>JC</p>		

**C32 Multi G4 / GZ4 / GX5.3 / G6.35 / GX6.35 Base Round Lampholder, Screw Mount**

		<p><b>4 to 6.35 MM PIN SPACING</b></p>	<ul style="list-style-type: none"> <li>- Round Steatite body</li> <li>- Copper, nickel-plated double wipe contacts with stainless steel reinforcing springs</li> <li>- Standard lead wires are 18 AWG SEW-1 (SF1) 200°C, 12" long, stripped 1/2"</li> <li>- Multi-pin base provides maximum flexibility and reduces inventory costs</li> <li>- Mounts using 2 screws in recessed nests through socket body</li> <li>- Other wire types, lengths and terminations are available upon request, contact the factory</li> <li>- Rated 8A 24V</li> <li>- cULus Listed</li> </ul>
<p>MR11 + MR16</p>	<p>JC</p>		

**C36 Multi G4 / GZ4 / GX5.3 / G6.35 / GX6.35 Base Lampholder with 1/8" IPS Hickey**

		<p><b>4 to 6.35 MM PIN SPACING</b></p>	<ul style="list-style-type: none"> <li>- Round Steatite body</li> <li>- Copper, nickel-plated double wipe contacts with stainless steel reinforcing springs</li> <li>- Standard lead wires are 18 AWG SEW-1 (SF1) 200°C, 12" long, stripped 1/2"</li> <li>- Multi-pin base provides maximum flexibility and reduces inventory costs</li> <li>- Mounts on 1/8" IPS pipe through attached hickey</li> <li>- Brackets can be grounded upon request</li> <li>- Other wire types, lengths and terminations are available upon request, contact the factory</li> <li>- Rated 8A 24V</li> <li>- cULus / UL Listed</li> </ul>
<p>MR11 + MR16</p>	<p>JC</p>		

FOR MORE INFORMATION PLEASE CALL 1-800-661-9610 (HEAD OFFICE) 1-888-762-5384 (USA)

PLEASE CONSULT THE FACTORY FOR MORE PRODUCTS AND CUSTOMIZATION.  
PRODUCT DETAILS AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

