











# Line Volt Non-Programmable Thermostats Selection Guide

	Model	Specifications									
		Schedule Option	User interface	Temperature Scale (Mechanical only)	Thermometer (Mechanical only)	Color	Switching	Switching method	Maximum Load	Minimum Load	Built-in Ground Fault (For electric underfloor)
	TH450	Non Prog.	Soft Keys			White	SPST	TRIAC	2000 W @ 120 V 4000 W @ 240 V	150 W @ 120 V 300 W @ 240 V	
	TH401	Non Prog.	Soft Keys			White	SPST	TRIAC	2500 W @ 240 V 1250 W @ 120 V	200 W @ 240 V 100 W @ 120 V	
	TH401-P10	Non Prog.	Soft Keys			White	SPST	TRIAC	2500 W @ 240 V 1250 W @ 120 V	200 W @ 240 V 100 W @ 120 V	
	TH108PLUS	Non Prog.	Soft Keys			White	SPST	TRIAC	3000 W @ 240 V	500 W @ 240V	
	TH108PLUS-P10	Non Prog.	Soft Keys			White	SPST	TRIAC	3000 W @ 240 V	500 W @ 240V	
	TH108-A-347S3	Non Prog.	Soft Keys			White	SPST	TRIAC	4335 W @ 347 V	700 W @ 347 V	
	TH114-A-120S	Non Prog.	Soft Keys			White	SPST	Relay	2000 W @ 120 V		
	TH114-A-240S-B	Non Prog.	Soft Keys			White	SPST	Relay	4000 W @ 240 V		
	TH114-A-240D-B	Non Prog.	Soft Keys			White	DPST	Relay	3600 W @ 240 V		
	TH114-AF-GA	Non Prog.	Soft Keys			White	DPST	Relay	1800 W @ 120 V 3600 W @ 240 V		5 mA GFCI
	TH114-AF-GB	Non Prog.	Soft Keys			White	DPST	Relay	1800 W @ 120 V 3600 W @ 240 V		15 mA EGFPD
	TL5110A1018	Non Prog.	Soft Keys			White	SPST	TRIAC	3000 W @ 240 V 1500 W @ 120 V	500 W @ 240 V 250 W @ 120 V	
	TL7135A1005	Non Prog.	Soft Keys			White	SPST	Relay	4000 W @ 240 V 3470 W @ 208 V		
	TL7235A1003	Non Prog.	Soft Keys			White	DPST	Relay	3600 W @ 240V 3120 W @ 208 V		
	TL116A1008	Non Prog.	Dial	°C		White	SPST	Snap-Acting Switch	3000 W @ 240 V 1500 W @ 120 V	300 W @ 240 V 150 W @ 120 V	
	TL116A1016	Non Prog.	Dial	°F		White	SPST	Snap-Acting Switch	3000 W @ 240 V 1500 W @ 120 V	300 W @ 240 V 150 W @ 120 V	
	T410A1013	Bi-metallic	Dial	°F		Premier White	SPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T410A1021	Bi-metallic	Dial	°C		Premier White	SPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T410A1047	Bi-metallic	Dial	°C		Beige	SPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T410B1004	Bi-metallic	Dial	°F		Premier White	DPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T410B1129	Bi-metallic	Dial	°C		Premier White	DPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T4398A1005	Diaphragm	Dial	°C	•	Premier White	SPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T4398A1021	Diaphragm	Dial	°F	•	Premier White	SPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T4398B1003	Diaphragm	Dial	°C	•	Premier White	DPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T4398B1029	Diaphragm	Dial	°F	•	Premier White	DPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T498A1778	Bi-metallic	Dial	°F	•	Premier White	SPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T498A1786	Bi-metallic	Dial	°C		Brush Gold	SPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T498A1810	Bi-metallic	Dial	°F		Brush Gold	SPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T498A1927	Bi-metallic	Dial	°C		Premier White	SPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T498B1512	Bi-metallic	Dial	°F	•	Brush Gold	DPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T498B1553	Bi-metallic	Dial	°F		Brush Gold	DPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T498B1678	Bi-metallic	Dial	°C		Premier White	DPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		
	T498B1686	Bi-metallic	Dial	°C	•	Premier White	DPST	Snap-Acting Switch	22 A @ 120/208/240 V 19 A @ 277 V		