

OCC Portable Construction Heater

OCC-WB Unit Heater with Bracket

OCC-RF Hard-Wired Unit Heater



Grounded 3-Pronged Outlet (OCC, OCC-WB)



NEMA 6-30R
30A, 250VAC

Features

Color

- Standard: almond.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 240/208V, 1-phase.

Construction

- Handle may be used as a reel for the electric cable and as attach point for the bracket.
- 6 ft. (2 m) molded electric cable.
- Safely recessed thermostat knob reduces heater size to a minimum.

- High-limit temperature control with automatic reset.

Fan

- 300 cfm fan.

Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat.

Temperature rise

- 28 °C (51 °F).

Control

- Built-in thermostat included.

Features OCC

Fan

- Totally enclosed motor (-MF model).
- Open motor (-MO model).

Installation

- Must be plugged into a grounded 3-pronged outlet, 30A, 250VAC.

Note: Always unplug heater when not in use.

Warranty

- 2-year warranty against defects (-MO model).
- 3-year warranty against defects (-MF model).

Application

- Construction area, workshop, garage

Features OCC-WB

Fan

- Open motor.

Installation

- Wall or ceiling mounting using the supplied bracket which allow 360° rotation of the heater and prevent it from tipping over.
- Must be plugged into a grounded 3-pronged outlet, 30A, 250VAC.

Note: Always unplug heater when not in use.

Warranty

- 2-year warranty against defects.

Application

- Workshop, shed, garage.

Features OCC-RF

Fan

- Open motor.

Installation

- Hard-wired into an electrical junction box (not included).
- Wall or ceiling mounting using the supplied bracket which allow 360° rotation of the heater and prevent it from tipping over.

Warranty

- 2-year warranty against defects.

Application

- Workshop, shed, garage.

Models

Watts	Volts	Product # ¹	Price	Motor type	Grounded 3-pronged outlet	Weight lb	kg
4800/3600	240/208	OCC4800AM-MF-TB6	176.00	Enclosed	30A. 250VAC	16.0	7.3
4800/3600	240/208	OCC4800AM-MO-TB6	119.00	Open	30A. 250VAC	16.0	7.3
4800/3600	240/208	OCC4800AMWB-MO-TB6 ¹	149.00	Open	30A, 250VAC	16.0	7.3
4800/3600	240/208	OCC4800AMRF-MO-TB6 ¹	138.00	Open	-	16.0	7.3

¹ Mounting bracket included.
Standard color is almond.

