



A More Complete Clean



FOR CARPET, GROUT AND RUBBER FLOORS

ENCAPSULATION CLEANER

TECHNICAL DATA SHEET

PACKAGING	CODE
4 x 3.78 L (4 x 1 US gal)	2404277001

DESCRIPTION:

CAPTIV800 Encapsulation Cleaner is a highly effective, deep cleaning formulation that removes stubborn dirt, oily soil, and tough stains. CAPTIV800 dries quickly after application leaving no sticky residue that can accelerate re-soiling. CAPTIV800 is based on a special encapsulation/anti-soiling technology that continues to work after the surface dries to protect and to improve soil removal with the next vacuuming/mopping operation.

APPLICATION DILUTION

Extraction Cleaning	1:60 – 1:40
Bonnet Cleaning	1:40
Spot Cleaning	1:15
Grout & Kitchen Floors	1:30
Rubber Floors	1:60

USE DIRECTIONS:

Before using CAPTIV800 Encapsulation Cleaner on carpet, vacuum the carpet to remove loose soil. To ensure the carpet is colorfast to the cleaning solution, test the product on a concealed small area of rug. **EXTRACTION CLEANING:** Dilute 2-3 oz (60-90 ml) of CAPTIV800 per gallon (3.78 L) of water (1:60 to 1:40) and follow the machine directions. **BONNET CLEANING:** Dilute 3 oz (90 ml) of CAPTIV800 per gallon of water (1:40). Spray the solution over an absorbent bonnet and the section of carpet to be cleaned. Use Fas-Trak's Bonnit Brush for best results. **SPOT CLEANING:** Dilute 8 oz (240 ml) of CAPTIV800 per gallon of water (1:15) into a spray bottle. Apply directly to the spot/stain, place terry towel cloth on spot/stain and use body weight (foot pressure) to absorb spot/stain into the terry towel. Repeat as required to remove stain. We recommend Fas-Trak's Bonnit Bug for efficient spot removal. **GROUT & KITCHEN FLOORS:** Dilute 4 oz (120 ml) of CAPTIV800 per gallon (3.78 L) of water (1:30). Pour directly on grout to be cleaned. Agitate grout with nylon bristle brush. Pick up soiled solution with wet/dry vacuum. Allow to air dry. For larger areas, use autoscrubber or single disk rotary floor machine affixed Fas-Trak's Scrub Brush for best results. **RUBBER FLOORS:** Dilute 2 oz (60 ml) per gallon (3.78 L) of cold water (1:60) of CAPTIV800. Mop or autoscrub the floor. For stair treads, use nylon hand brush to agitate solution and pick up with wet/dry vacuum or microfiber cloth. Allow to air dry.

SECURITY:

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	X
X =	See SDS
0 =	Insignificant
1 =	Slight
2 =	Moderate
3 =	High
4 =	Extreme

TECHNICAL SPECIFICATIONS:

Appearance	Clear Liquid
Colour	Colourless
Odour	Acrylic
Phosphates	None
pH	8.0
Flash Point	>212 °F (100 °C)
Certification	The Carpet and Rug Institute

NOTE:

The data presented herein is based on experiments and information believed reliable. However, we can make no guarantee on performance of, or results obtained through the use of the product herein described owing to varying conditions in laboratories and plants over which we have no control. Neither can any guarantee be given that the products or uses outlined will not infringe any existing patents.



FOR A MORE COMPLETE CLEAN, CONTACT US!

AVMOR Ltd.
950 Michelin, Laval, Québec Canada H7L 5C1
Tel.: (450) 629-3800 Fax: (450) 629-4355
1 800 387-8074 client-service@avmor.com

avmor.com



Let's
CLEAN®

TRAINING
PROGRAMS
AVAILABLE