



1" Drive Scoop Tram Wheel Sockets

- Outside diameter of socket enables it to fit between the nut and the outer rim and wheel
- One piece construction

| 6 Point Part No. | Size | Overall Length (in.) | Weight (lbs.) |
|------------------|---------|----------------------|---------------|
| STW1.5 | 1-1/2" | 9 | 5.4 |
| STW1-516 | 1-5/16" | 9 | 5.4 |
| STW1-14 | 1-1/4" | 9 | 5.4 |



Swivel Wrenches

- Great for disassembly of groove joint couplings
- Tested for 190-200 ft. pounds

| 12 Point Part No. | Size | Overall Length (in.) | Weight (lbs.) |
|-------------------|------------------|----------------------|---------------|
| RSW1 | 7/8" X 1-1/16" | 10.50 | 1.8 |
| RSW2 | 7/8" X 11/16" | 10.50 | 1.8 |
| RSW3 | 9/16" X 3/4" | 10.50 | 1.8 |
| RSW4 | 1-1/4" x 1-7/16" | 10.50 | 2.0 |
| RSW5 | 1-1/4" x 1-5/8" | 13.75 | 4.0 |



Roofbolt Dollie with Steel Extension 1-1/8" 8 PT

| Part No. | Description | Overall Length (in.) | Weight (lbs.) |
|-----------|-----------------------|----------------------|---------------|
| RBD118L12 | with 12" of cut steel | 20.5 | 9.5 |
| RBD118L18 | with 18" of cut steel | 26.5 | 10 |
| RBD118L24 | with 24" of cut steel | 32.5 | 10.8 |
| RBD118L36 | with 36" of cut steel | 44.5 | 11.5 |
| RBD118L48 | with 48" of cut steel | 56.5 | 13 |



Roofbolt Dollie 1-1/8" 8 PT

| Part No. | Drive | Overall Length (in.) | Weight (lbs.) |
|-------------|------------------|----------------------|---------------|
| RBDR25118L | Rope Thread R25 | 8.5 | 4 |
| RBDR28118L | Rope Thread R28 | 8.5 | 4 |
| RBDR32118L | Rope Thread R232 | 8.5 | 4 |
| RBDR118L | 7/8" Hex | 8.5 | 4 |
| RBDR118L1/2 | 1/2" Square | 8.5 | 4 |
| RBDR118L3/4 | 3/4" Square | 8.5 | 4 |



Optional Leather Holder

12" Hammer Head Miner's Adjustable Wrench


- Special wide opening of 1 3/4"
- Same maximum opening as a 15" adjustable wrench at half the weight
- 7/8" hex opening in handle can be used for pulling drill steel and accommodates 1" up to 3" Victaulic couplings
- Part No: RS-12
- Part No: RSWH-1 optional leather holder



Optional Leather Holder

12" Miner's Adjustable Wrench

- Special wide opening of 1 3/4"
- Opens the same size as a 15" adjustable wrench at half the weight
- 7/8" hex opening in handle can be used for pulling drill steel and accommodates 1" up to 3" Victaulic couplings
- Part No: RS-12H
- Part No: RSWH-1 optional leather holder



DYWIDAG Rod Installation Tool

- Spin adapters for #6/#7/#8 DYWIDAGG
- 7/8" hex drive

| Part No. | Size | Overall Length (in.) | Weight (lbs.) |
|----------|------|----------------------|---------------|
| DSA6 | #6 | 9 | 2 |
| DSA7 | #7 | 9 | 2 |
| DSA8 | #8 | 9 | 2 |