



## PSG30E12SP

UPC:786685520926

### Dimensions:

- **Height:** 110 IN
- **Length:** 100.6 IN
- **Width:** 32 IN

**Weight:** .2 LB

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Special Features:** Varistor transient surge voltage, surge voltage protection against internal surge, safety class 1 with ground connection
- **Wattage:** 30W
- **Operating Temperature - Max:** 75 C
- **Operating Temperature - Min:** -20 C
- **Enclosure Material:** Plastic
- **Output Voltage:** 12V
- **Series:** PSG
- **Terminals:** Heavy-duty screw
- **Phase:** Single-phase

### Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [PSG30E12SP AutoCAD 2D Footprint \(mm\)](#)
- [PSG30E12SP 3D Model Xchange](#)
- [PSG30E12SP 2D Drawing Xchange](#)
- [PSG30E12SP 2D PDF](#)
- [PSG30E12SP AutoCAD 2D Footprint](#)
- [PSG30E12SP 3D Inventor](#)
- [Installation Instructions for PSG240F Power Supply](#)

- [Eaton's PSG Series Power Supplies](#)
- [Eaton Specification Sheet - PSG30E12SP](#)

**Certifications:**

- cUL Certified
- cULus/UL 60950-1
- EN Listed
- UL 508
- IEC Rated
- CSA Certified

**Product compliance:**

- CE Marked
- RoHS Compliant
- German Safety