



## PSG60E24RM

UPC:786685520971

### Dimensions:

- **Height:** 160 IN
- **Length:** 55 IN
- **Width:** 150 IN

**Weight:** .37 LB

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Special Features:** Varistor transient surge voltage, surge voltage protection against internal surge, safety class 1 with ground connection
- **Wattage:** 60W
- **Operating Temperature - Max:** 75 C
- **Operating Temperature - Min:** -20 C
- **Enclosure Material:** Metal
- **Output Voltage:** 24V
- **Series:** PSG
- **Terminals:** Removable
- **Phase:** Single-phase

### Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [PSG60E24RM AutoCAD 2D Footprint \(mm\)](#)
- [PSG60E24RM 3D Inventor](#)
- [PSG60E24RM AutoCAD 2D Footprint](#)
- [PSG60E24RM 3D Model Xchange](#)
- [PSG60E24RM 2D Drawing Xchange](#)
- [PSG60E24RM 2D PDF](#)
- [Installation Instructions for PSG60E Power Supply](#)

- [Eaton's PSG Series Power Supplies](#)
- [Eaton Specification Sheet - PSG60E24RM](#)

**Certifications:**

- CSA Certified
- EN Listed
- cUL Certified
- IEC Rated
- UL 508
- cULus/UL 60950-1

**Product compliance:**

- CE Marked
- German Safety
- RoHS Compliant