

PSG120E24RM

UPC:786685520988

Dimensions:

- **Height:** 76.2 MM
- **Length:** 98 MM
- **Width:** 50 MM

Weight:1.59 G

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Special Features:** Varistor transient surge voltage, surge voltage protection against internal surge, safety class 1 with ground connection
- **Wattage:** 120W
- **Operating Temperature - Max:** 75 C
- **Operating Temperature - Min:** -20 C
- **Enclosure Material:** Metal
- **Input Voltage:** 100-240V
- **Output Voltage:** 24V
- **Series:** PSG
- **Terminals:** Removable
- **Phase:** Single-phase

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [PSG120E24RM AutoCAD 2D Footprint \(mm\)](#)
- [PSG120E24RM 2D Drawing Xchange](#)
- [PSG120E24RM 3D Model Xchange](#)
- [PSG120E24RM AutoCAD 2D Footprint](#)
- [PSG120E24RM 2D PDF](#)
- [PSG120E24RM 3D Inventor](#)
- [Eaton Specification Sheet - PSG120E24RM](#)



Certifications:

- cUL Certified
- CSA Certified
- IEC Rated
- UL 508
- cULus/UL 60950-1
- EN Listed

Product compliance:

- CE Marked
- RoHS Compliant
- German Safety