

Eaton S801 series soft starter

S801+R13N3S

UPC:786685558813

Dimensions:

- **Height:** 11.7 IN
- **Length:** 11.1 IN
- **Width:** 8.7 IN

Weight:12.4 LB

Notes:All units require a 24 Vdc power supply found on catalog Page V6-T1-85, or equivalent., S811+T_, S811+U_ and S811+V_ units require lug kits, S811+U50_ unit does not have IEC certification.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Amperage Rating:** 135A
- **Communication:** Modbus RTU
- **Display Material:** LCD
- **Frame Size:** R-frame
- **Frequency Rating:** 47-63 Hz
- **Maximum Ac Current:** 240 Vac
- **Maximum Dc Current:** 120 Vdc
- **Module Interface:** CIM
- **Nema Rating:** NEMA Type 0
- **Number Of Conductors:** 2-Jan
- **Number Of Poles:** Three-pole
- **Operating Temperature:** -30° to 50°C
- **Operating Voltage:** 200-600V
- **Power Supply:** 24V
- **Size:** NEMA 0
- **Type:** Soft starter
- **Used With:** Three-phase motors



- **Wire Size:** #22-14 AWG

Supporting documents:

- [Eatons Volume 6-Solid-State Motor Control](#)
- [Instructions for S801+ Soft Starter, S801+N... and S801+R](#)
- [S811+/S801+ soft starters](#)
- [Eaton Specification Sheet - S801+R13N3S](#)

Certifications:

- CSA Certified
- IEC 947
- EN 60947-4-2
- CSA Certified for Elevator Duty

Product compliance:

- CE Marked