

S811+ Soft Starter with Digital Interface Module

S811+R10P3S

UPC:786685558950

Dimensions:

- **Height:** 7.92 IN
- **Length:** 6.64 IN
- **Width:** 4.38 IN

Weight:10.5 LB

Notes:All units require a 24 Vdc power supply found on catalog Page V6-T1-85, or equivalent., S811+T_, S811+U_ and S811+V_ units require lug kits, S811+U50_ unit does not have IEC certification.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Options:** Premium, 600V rated, Level/Edge Sense, Inline or Inside-the-Delta wiring configuration, pump control and extended ramp
- **Amperage Rating:** 1000A
- **Communication:** Modbus RTU
- **Configuration:** Inline (default) or inside the delta
- **Display Material:** LCD
- **Frame Size:** R-frame
- **Frequency Rating:** 47-63 Hz
- **Maximum Ac Current:** 240 Vac
- **Maximum Dc Current:** 120 Vdc
- **Module Interface:** Digital interface module
- **Nema Rating:** NEMA Type 0
- **Number Of Conductors:** 2-Jan
- **Number Of Poles:** Three-pole



- **Operating Temperature:** -30° to 50°C
- **Operating Voltage:** 200-600V
- **Power Supply:** 24V
- **Size:** NEMA 0
- **Type:** Soft starter
- **Used With:** Three-phase motors
- **Wire Size:** #14-4/0 AWG

Supporting documents:

- [Eatons Volume 2-Commercial Distribution](#)
- [Product Datasheet - S811+R10P3S](#)
- [Type S811+ Soft Starter - R-frame](#)
- [Instructions for S811+ Soft Starter, S811+N... and S811+R](#)
- [S811+/S801+ soft starters](#)
- [Eaton Specification Sheet - S811+R10P3S](#)

Certifications:

- CSA file No. 3211-06
- IEC 60947-4-2
- UL Recognized
- UL Listed
- EN 60947-4-2
- CSA Certified for Elevator Duty

Product compliance:

- CE Marked