

## Eaton Bussmann series FWH high speed fuse

**FWH-10A14F**

**UPC:**051712370806

### Dimensions:

- **Height:** 14 MM
- **Length:** 51 MM
- **Width:** 14 MM

**Weight:**21.6 G

### Warranties:

- Not Applicable

### Specifications:

- **Type:** High speed fuse
- **Application:** protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
- **Voltage Rating:** 1000 Vac, 800 Vdc
- **Voltage Rating Numeric:** 500 V
- **Amperage Rating:** 10A
- **Amperage Rating Numeric:** 10 A
- **Interrupt Rating:** 200 kAIC Vac, 50 kAIC at 500 Vdc
- **Connection:** Ferrule end X ferrule end
- **Construction Size:** 14 x 51 mm
- **Packaging Type:** Standard
- **Breaking Capacity:** 200 A
- **Clearing (I<sup>2</sup>T):** Clearing at 500V: 13
- **Frequency Rating Maximum:** 62 HZ
- **Frequency Rating Minimum:** 45 HZ
- **Fuse Shape:** cylindrical
- **Fuse Indicator:** Non Indicating
- **Pre Arc (I<sup>2</sup>T):** 3.6
- **Release Characteristic:** Other
- **Utilization category:** aR (accompanied semiconductor protection)



- **Voltage Type:** AC/DC
- **Watt Losses:** 4W
- **With Striker:** No

**Supporting documents:**

- [Product Catalog](#)
- [500V 10Amp S/COND FERRULE 14.3 X 50.8MM](#)

**Certifications:**

- UL Recognized
- CSA Certified

**Product compliance:**

- CE Marked