

## Eaton Bussmann series low voltage cylindrical fuse

**C10G10**

**UPC:**051712754262

**Dimensions:**

- **Height:** 38 MM
- **Length:** 38 MM
- **Width:** 10 MM

**Weight:**38 G

**Warranties:**

- 1 year limited

**Specifications:**

- **Type:** fuse
- **Application:** for industrial applications | for general purpose use
- **Voltage Rating:** 500V
- **Voltage Rating Numeric:** 500 V
- **Amperage Rating:** 10A
- **Amperage Rating Numeric:** 10 A
- **Interrupt Rating:** 120 kAIC
- **Class:** Class C gL/gG
- **Connection:** Ferrule end X ferrule end
- **Construction Size:** 10 x 38 mm
- **Material Type:** Ceramic body, Silver-plated copper endcap
- **Packaging Type:** Standard
- **Quantity:** 10 per package
- **Fuse Indicator:** CHM fuse holder
- **Fuse Type:** Cylindrical
- **Breaking Capacity:** 120 KA
- **Frequency Rating Maximum:** 45 HZ
- **Frequency Rating Minimum:** 62 HZ
- **Fuse Shape:** cylindrical
- **Release Characteristic:** Other
- **Utilization Category:** gL/gG (cable)

protection/equipment protection)

- **Voltage Type:** AC
- **With Striker:** No

**Supporting documents:** No Data

**Certifications:**

- IEC 60269
- VDE

**Product compliance:**

- Contact factory
- CE Marked
- GoST-R
- RoHS Compliant