

Eaton Bussmann series low voltage cylindrical fuse

C22G100

UPC:051712754514

Dimensions:

- **Height:** 58 MM
- **Length:** 58 MM
- **Width:** 22.2 MM

Weight:58 G

Warranties:

- 1 year limited

Specifications:

- **Type:** fuse
- **Application:** for industrial applications | for general purpose use
- **Voltage Rating:** 500V
- **Voltage Rating Numeric:** 500 V
- **Amperage Rating:** 100A
- **Amperage Rating Numeric:** 100 A
- **Class:** Class C gL/gG
- **Connection:** Ferrule end X ferrule end
- **Construction Size:** 22 x 58 mm
- **Material Type:** Ceramic body, Silver-plated copper endcap
- **Packaging Type:** Standard
- **Quantity:** 10 per package
- **Fuse Indicator:** CH22 fuse holder
- **Fuse Type:** Cylindrical
- **Breaking Capacity:** 120 KA
- **Frequency Rating Maximum:** 45 HZ
- **Frequency Rating Minimum:** 62 HZ
- **Fuse Shape:** cylindrical
- **Release Characteristic:** Other
- **Utilization Category:** gL/gG (cable protection/equipment protection)



- **Voltage Type:** AC
- **With Striker:** No

Supporting documents:

- [Product Catalog](#)

Certifications:

- IEC 60269
- VDE

Product compliance:

- Contact factory
- CE Marked
- GoST-R
- RoHS Compliant