# Eaton Bussmann series low voltage cylindrical fuse

#### C22G10S

UPC:051712668439

### **Dimensions:**

Height: 22 MMLength: 58 MMWidth: 22 MM

Weight:55.9 G

#### Warranties:

• 1 year limited

## **Specifications:**

• Type: fuse

• Special Features: Striker

 Application: for industrial applications | for general purpose use

Voltage Rating: 690V

• Voltage Rating Numeric: 690 V

• Amperage Rating: 10A

• Amperage Rating Numeric: 10 A

• Interrupt Rating: 80 kAIC

• Class: Class C gL/gG

• Construction Size: 22 x 58 mm

• Material Type: Ceramic body, Silver-plated

copper endcap

• Mounting: Holder

• Packaging Type: Standard

• Quantity: Qty 10

Fuse Indicator: with striker
Breaking Capacity: 80 KA

• Frequency Rating Maximum: 45 HZ

• Frequency Rating Minimum: 62 HZ

• Fuse Shape: cylindrical

• Release Characteristic: Other

• Utilization Category: gL/gG (cable



# protection/equipment protection)

Voltage Type: ACWith Striker: Yes

## **Supporting documents:**

Product Catalog

## **Certifications:**

• IEC 60269

# **Product compliance:**

- Contact factory
- RoHS Compliant
- CE Marked

© 2016 Eaton. All rights reserved.