

Eaton definite purpose contactor

C25GNF390T

UPC:782114100196

Dimensions:

- **Height:** 3.75 IN
- **Length:** 3.97 IN
- **Width:** 2.63 IN

Weight:3 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
- 1 year

Specifications:

- **Accessories:** Mounting plate
- **Connection:** Quick
- **Amperage Rating:** 120A
- **Auxiliary Contact:** Quick connect (side-by-side)
- **Coil:** 24 Vac, 50/60 Hz
- **Contact Configuration:** 1NO, 1NC
- **Enclosure:** Open with metal mounting plate
- **Frame Size:** 15-50A, two- and three-pole
- **Model:** Contactor
- **Number Of Poles:** Three-pole
- **Options:** Individual pkg.
- **Resistive Load:** 140A
- **Series:** F1
- **Terminals:** Box lugs (posidrive setscrew)
- **Type:** Non-reversing

Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [C25GNF3 3D Inventor](#)



- [C25GNF3 3D Model Xchange](#)
- [C25GNF3 2D Drawing Xchange](#)
- [C25GNF3 AutoCAD 2D Footprint \(mm\)](#)
- [C25GNF3 2D PDF](#)
- [C25GNF3 AutoCAD 2D Footprint](#)
- [Eaton Specification Sheet - C25GNF390T](#)

Certifications:

- CSA Certified
- UL Listed file E1491 (Guide Number NLDX2)
- UL Recognized

Product compliance:

- RoHS Compliant
- CE Marked