

Eaton definite purpose contactor

C25LNE3360A

UPC:782114181584

Dimensions:

- **Height:** 13.12 IN
- **Length:** 7.78 IN
- **Width:** 7.05 IN

Weight:27.7 LB

Notes:Resitive Load rating per pole

Warranties:

- 1 year

Specifications:

- **Connection:** Quick
- **Amperage Rating:** 360A
- **Coil:** 110-120 Vac, 50/60 Hz
- **Contact Configuration:** 1NO, 1NC
- **Enclosure:** Open with metal mounting plate
- **Frame Size:** 15-50A, two- and three-pole
- **Model:** Contactor
- **Number Of Poles:** Three-pole
- **Size:** 360A, three-pole
- **Terminals:** Box lugs (posidrive setscrew)
- **Type:** Non-reversing

Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [C25LNE3 2D Drawing Xchange](#)
- [C25LNE3 2D PDF](#)
- [C25LNE3AutoCAD 2D Footprint \(mm\)](#)
- [C25LNE3 3D Inventor](#)
- [C25LNE3 3D Model Xchange](#)
- [C25LNE3 AutoCAD 2D Footprint](#)
- [Eaton Specification Sheet - C25LNE3360A](#)

Certifications:



- UL Recognized
- CSA Certified

Product compliance:

- RoHS Compliant

© 2016 Eaton. All rights reserved.