

## Eaton Enhanced 50 photoelectric sensor

1351E-8514

UPC:782116111688

### Dimensions:

- **Height:** 3.46 IN
- **Length:** 1.91 IN
- **Width:** 1.81 IN

**Weight:**.5375 LB

### Warranties:

- 3 year

### Specifications:

- **Connection:** 6.6 Ft. (2m) Cable
- **Contact Rating:** 3A at 240 Vac
- **Cable Type:** PVC
- **Contact Configuration:** SPDT Form C relay
- **Cord Length:** 79.2 FT
- **Enclosure Material:** Fiberglass reinforced plastic
- **Environmental Rating:** IP 67, IP69K
- **Input Voltage:** 12–240 Vdc 24–240 Vac
- **Led Indicators:** Yellow power on, green outout status, red marginal gain
- **Maximum Ac Current:** 3A
- **Operating Mode:** Diffuse Reflective
- **Operating Temperature:** -13° to 131°F (-25° to 55°C)
- **Switch Type:** Photoelectric
- **Time Delay:** Yes

### Supporting documents:

- [Eatons Volume 8-Sensing Solutions](#)
- [Eaton Specification Sheet - 1351E-8514](#)

### Certifications:

- CSA Certified



**Product compliance:**

- Contact Manufacturer
- RoHS Compliant

---

© 2016 Eaton. All rights reserved.