

## Flexible cord Steel fittings


- Made of corrosion-resistant, zinc-plated machined steel
- Raintight and strain relieving
- Neoprene rubber bushing ensures a permanent raintight seal around the cord outer jacket.
- Galvanized steel pressure ring prevents distortion of the bushing when subjected to the tightening of the gland nut



Cat. no.	Trade size (in.)	KO size (in.)	Cable dimensions (in.)		Throat (in.)	Dimensions (in.)		
			Min.	Max.		A	B	C
<b>Cord grip fittings (machined steel / zinc plated)</b>								
CICG50A250	1/2	1/2	0.150	0.250	0.640	1 1/32	13/16	1 5/16
CICG50A350	1/2	1/2	0.250	0.350	0.640	1 1/32	13/16	1 5/16
CICG50A450	1/2	1/2	0.350	0.460	0.640	1 1/32	13/16	1 5/16
CICG50A560	1/2	1/2	0.450	0.560	0.640	1 1/32	13/16	1 5/16
CICG50A650	1/2	1/2	0.560	0.650	0.640	1 1/32	13/16	1 5/16
CICG75A250	3/4	3/4	0.150	0.250	0.687	1 1/32	13/16	1 5/16
CICG75A350	3/4	3/4	0.250	0.350	0.687	1 1/32	13/16	1 5/16
CICG75A450	3/4	3/4	0.350	0.460	0.687	1 1/32	13/16	1 5/16
CICG75A560	3/4	3/4	0.450	0.560	0.687	1 1/32	13/16	1 5/16
CICG75A650	3/4	3/4	0.550	0.650	0.687	1 1/32	13/16	1 5/16
CICG75B750	3/4	3/4	0.650	0.750	0.845	1 1/4	1 1/32	1 9/16
CICG75B850	3/4	3/4	0.750	0.850	0.845	1 1/4	1 1/32	1 9/16
CICG100B560	1	1	0.450	0.560	0.937	1 1/4	1 1/8	1 3/4
CICG100B650	1	1	0.560	0.650	0.937	1 1/4	1 1/8	1 3/4
CICG100B750	1	1	0.650	0.750	0.937	1 1/4	1 1/8	1 3/4
CICG100B850	1	1	0.750	0.850	0.937	1 1/4	1 1/8	1 3/4
CICG100C950	1	1	0.850	0.950	1.050	1 1/2	1 3/16	1 7/8
CICG100C1050	1	1	0.950	1.050	1.050	1 1/2	1 3/16	1 7/8
CICG125C850	1 1/4	1 1/4	0.750	0.850	1.187	1 1/2	1 1/4	1 5/16
CICG125C950	1 1/4	1 1/4	0.850	0.950	1.187	1 1/2	1 1/4	1 5/16
CICG125D1050	1 1/4	1 1/4	0.950	1.050	1.375	2	1 1/4	1 5/16
CICG125D1150	1 1/4	1 1/4	1.050	1.150	1.375	2	1 1/4	1 5/16
CICG125D1250	1 1/4	1 1/4	1.150	1.250	1.375	2	1 1/4	1 5/16
CICG125D1375	1 1/4	1 1/4	1.250	1.375	1.375	2	1 1/4	1 5/16
CICG150D1050	1 1/2	1 1/2	0.950	1.050	1.375	2	1 5/16	2
CICG150D1150	1 1/2	1 1/2	1.050	1.150	1.375	2	1 5/16	2
CICG150D1250	1 1/2	1 1/2	1.150	1.250	1.375	2	1 5/16	2
CICG150D1375	1 1/2	1 1/2	1.250	1.375	1.375	2	1 5/16	2




CICG50A250 / CICG150D1375



<b>90° cord grip fittings (malleable iron)</b>								
CICG9050-A250	1/2	1/2	0.150	0.250	0.609	1 1/8	9/16	1 21/32
CICG9050-A350	1/2	1/2	0.250	0.350	0.609	1 1/8	9/16	1 21/32
CICG9050-A450	1/2	1/2	0.350	0.450	0.609	1 1/8	9/16	1 21/32
CICG9050-A560	1/2	1/2	0.450	0.560	0.609	1 1/8	9/16	1 21/32
CICG9050-A650	1/2	1/2	0.550	0.650	0.609	1 1/8	9/16	1 21/32
CICG9075-A250	3/4	3/4	0.150	0.250	0.813	1 3/8	19/32	1 25/32
CICG9075-A350	3/4	3/4	0.250	0.350	0.813	1 3/8	19/32	1 25/32
CICG9075-A450	3/4	3/4	0.350	0.450	0.813	1 3/8	19/32	1 25/32
CICG9075-A560	3/4	3/4	0.450	0.560	0.813	1 3/8	19/32	1 25/32
CICG9075-A650	3/4	3/4	0.550	0.650	0.813	1 3/8	19/32	1 25/32
CICG9075-B750	3/4	3/4	0.650	0.750	0.813	1 3/8	19/32	1 25/32
CICG9075-B850	3/4	3/4	0.750	0.850	0.813	1 3/8	19/32	1 25/32



CICG9050-A250 / CICG9075-B850



## Flexible cord Nonmetallic fittings

- Liquidtight and strain relieving (IP68)
- Corrosion-resistant polyamide (nylon)
- Superior anti-vibration protection
- Acme threads on body prevent skipping and speed installation
- Indoor or outdoor use
- Quick installation
- Working temperatures:  
Static: -40 °C to 115 °C  
Dynamic: -20 °C to 100 °C
- Resistant to: Salt water, weak acids, gasoline, alcohol, oil, grease and common solvents



Cat. no.	Trade size (in.)	KO size (in.)	Dia. over cable jacket (in.)		Throat (in.)	Dimensions (in.)			
			Min.	Max.		A	B	C	
<b>"Skintight" straight cord fittings (nylon)</b>									
CISLR-9-03*	3/8	3/8	0.069	0.187	0.375	3/4	31/32	17/32	
CISLR-9-03*	3/8	3/8	0.115	0.312	0.375	3/4	31/32	17/32	
CISLR-13-04	1/2	1/2	0.170	0.450	0.500	15/16	1 3/32	5/8	
CISLR-13-04	1/2	1/2	0.230	0.546	0.500	1 1/16	1 7/32	5/8	
CISLR-21-04	1/2	1/2	0.250	0.485	0.600	1 9/32	1 11/32	5/8	
CISLR-21-06	3/4	3/4	0.250	0.485	0.667	1 7/16	1 11/32	5/8	
CISLR-21-06	3/4	3/4	0.450	0.709	0.667	1 7/16	1 11/32	5/8	
<b>90° "skintight" cord fittings (nylon)</b>									
CISLFR-9-03*	3/8	3/8	0.065	0.230	0.375	3/4	2 7/16	7/32	
CISLF-9-03*	3/8	3/8	0.105	0.315	0.375	3/4	2 7/16	7/32	
CISLFR-13-04	1/2	1/2	0.095	0.290	0.500	15/16	3 15/32	5/8	
CISLF-13-04	1/2	1/2	0.170	0.450	0.500	15/16	3 15/32	5/8	
CISLFR-21-06	3/4	3/4	0.250	0.490	0.667	1 7/16	4 17/32	5/8	
CISLF-21-06	3/4	3/4	0.435	0.705	0.667	1 7/16	4 17/32	5/8	

\* UL Recognized



	Cat. no.	Trade size (in.)	KO size (in.)	Clamping range (in.)	
				Min.	Max.
<b>Nonmetallic fittings</b>					
Dry location	CI3360	1/2	1/2	0.30	0.60

CI3360



Complete with metric locknut. Working temperatures : -30 °C (-22 °F) to 80 °C (176 °F)

Cat. no.	Trade size (in.)
<b>Nylon locknuts</b>	
CI1703-PL*	3/8
CI1704-PL*	1/2
CI1706-PL*	3/4



CI1703-PL\* / CI1706-PL\*

\* Not CSA certified