



DUAL FUNCTION TAMPER-RESISTANT 20A AFCI/GFCI RECEPTACLE, WHITE

AFGF202TRW | [radiant](#)

FEATURES & BENEFITS

Pass & Seymour® Dual-Function AFCI/GFCI Receptacles are the latest innovation in electrical safety, and a code-approved alternative to dual-function AFCI/GFCI breakers. Designed to protect against electrical fires caused by arc faults and injury due to electrical shock, these new devices are compliant with NEC® AFCI and GFCI requirements in kitchens and laundry areas for new construction, circuit modifications/extensions and replacement receptacles.

radiant® Screwless Wall Plate not included.

For detailed GFCI receptacle information, visit our [GFCI Headquarters](#).

For detailed AFCI receptacle information, visit our [AFCI Headquarters](#).

Visit NEMA's [website](#) for more information on all things AFCI.

For detailed Tamper-Resistant receptacle information, visit our [Tamper-Resistant Receptacles page](#).

- Part of the all-new radiant® collection.
- **FSUL Listed** (Federal Specification WC596)
- **Feed-through protection.**
- **Two back-wire holes per termination** add wiring flexibility, eliminate pigtail and save box space.
- **High-impact-resistant, thermoplastic construction** for superior strength and durability.
- **Tamper-Resistant** automatic shutter system prevents young children from inserting common household objects. Black shutters essentially "disappear" into the background for an invisible effect preferred by end users.
- **Ground terminal back-wire** for fast installation.
- **Patented SafeLock® Protection** - if critical components are damaged and ground fault protection is lost, power to the receptacle is disconnected.
- **Two indicator lights**, one for GFCI and one for AFCI. Easy to distinguish between trip caused by arc fault and trip caused by ground fault. GFCI indicator light flashes if device fails the self-test, signaling that the GFCI should be replaced.
- **Auto-ground clip** assures a positive ground to metal box.
- **Prevents line-load miswire** - no power to the face or downstream receptacles if wired incorrectly.

SPECIFICATIONS

GENERAL INFO

Color: White

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

cULus: Yes

Federal Spec: Yes

UL Standard: UL943, UL1699

CONSTRUCTION INFORMATION

Component 4: 78500705580

TECHNICAL INFORMATION

Amps: 20A

NEMA Configuration Number: 5-20R

Volts: 125

COUNTRY OF ORIGIN

Country Of Origin: CHINA