

**CADDY®**

# CADDY® PYRAMID Tool-Free Supports

## Features

- Push-in clamps install without the need for additional tools or strut clamps
- Ready to use out of the box, saving installation time and labor
- Plastic clamps and base will not corrode pipe
- Foam bottom offers low abrasion interface for better roof membrane protection
- Provides superior load distribution, even with varying rooftop surfaces
- Compatible with roof surfaces including single ply, bituminous, metal and spray foam
- Easy to transport to the roof
- Supports green building requirements; thermoplastic bases are made from recycled material and can contribute to earning LEED credits



The CADDY® PYRAMID Tool-Free series offers a unique labor saving solution for supporting electrical and mechanical applications on a variety of roof surfaces. The CADDY PYRAMID Tool-Free series restrains pipe and conduit without the need for strut clamps or installation tools. Superior load distribution and a low abrasion foam interface combine to ensure that the roof membrane is protected despite varying roof surfaces and shifting caused by expansion and contraction.



**ERICO®**

## CADDY® PYRAMID Tool-Free Support Kit

Material: Polyethylene; Polypropylene; Nylon




Temperature: -50 to 150 °F

Static Load Safety Factor: 3:1

Part Number	Length 1 L1	Length 2 L2	Length 3 L3	Width W	Height H	A	B	Surface Area	Unit Weight	Static Load F
PTF6	8"	–	3.2"	6"	4"	3.2"	0.8"	41 in <sup>2</sup>	0.6 lb	300 lb
PTF10	12 1/2"	4.8"	6.4"	8"	4"	6.4"	0.8"	92 in <sup>2</sup>	1.0 lb	1,000 lb
PTF16	19"	8.0"	9.6"	8"	4"	9.6"	0.8"	142 in <sup>2</sup>	2.0 lb	1,500 lb

Length 2 represents maximum pipe center to pipe center using PTF2C clamps. Length 3 represents maximum pipe center to pipe center using PTF1C clamps.

Part Number	Number of Clamps Includes		Maximum Clamp Capacity	
	PTF1C	PTF2C	PTF1C	PTF2C
PTF6	1	–	3	1
PTF10	–	2	5	2
PTF16	–	2	7	3



## CADDY® PYRAMID Tool-Free Clamp



### Features

- Push-in clamps install without the need for additional tools or strut clamps
- Clamps come in two different sizes to fit project needs
- Plastic clamps and base will not corrode pipe

Material: Nylon

Temperature: -50 to 150 °F

Part Number	Outer Diameter OD	Length L	Width W	A	Unit Weight
PTF1C	0.50" – 1.32"	1.6"	3/4"	3/8"	0.025 lb
PTF2C	0.84" – 2.38"	3.2"	3/4"	3/8"	0.045 lb



### WARNING

ERICO products shall be installed and used only as indicated in ERICO product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.

Copyright ©2015 ERICO International Corporation. All rights reserved.

CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.