

Service Entrance Cable

Connectors and Entrance Heads



CI808 / CI816

CI806

CI804



Zinc Die Cast Locknut



Zinc Die Cast Locknut



Cat. No.	Trade Size (in.)	Clamping Range (in.)		Throat (in.)
		Min.	Max.	
Two Screw Fittings (Zinc Alloy)				
CI804	3/8	0.18	0.64	0.64
CI806	3/4	0.41	0.82	0.83
CI808	1	0.50	1.04	1.05
CI810	1-1/4	0.56	1.06	1.37
CI812	1-1/2	0.63	1.60	1.81
CI816	2	0.86	2.06	2.05

NOTE : 3/8 in. trade size connectors require a 1/2 in. knockout.

CIEFA-1/2 / CIEFA-4



CIEFSA-1/2 / CIEFSA-4



Cat. No.	Trade Size (in.)
Service Entrance Heads (Cast Aluminum)	
Rigid Conduit	
CIEFA-1/2	1/2
CIEFA-3/4	3/4
CIEFA-1	1
CIEFA-1 1/4	1-1/4
CIEFA-1 1/2	1-1/2
CIEFA-2	2
CIEFA-2 1/2	2-1/2
CIEFA-3	3
CIEFA-3 1/2	3-1/2
CIEFA-4	4
Service Entrance Heads (Cast Aluminum)	
EMT	
CIEFSA-1/2	1/2
CIEFSA-3/4	3/4
CIEFSA-1	1
CIEFSA-1 1/4	1-1/4
CIEFSA-1 1/2	1-1/2
CIEFSA-2	2
CIEFSA-2 1/2	2-1/2
CIEFSA-3	3
CIEFSA-3 1/2	3-1/2
CIEFSA-4	4

Trade Size (in.)	KO Dimensions (in.)		
	Small	Large	Center
1/2	0.312	—	—
3/4	0.375	0.400	—
1	0.438	0.500	—
1-1/4	0.438	0.625	—
1-1/2	0.610	0.750	0.400
2	0.750	1.000	0.525
2-1/2	0.875	1.300	1.000
3	1.125	1.750	1.125
3-1/2	1.125	1.750	1.125
4	1.125	1.750	1.125

