

**Liquidtight Flexible Metal Conduit Fittings****T&B Catalog Number:**

5710

UPC Number:

78621005710

Status:

Active

Description:

1/2 Inch neoprene liquidtight knockout plug.

Features

Made of flame retardant neoprene, these new knockout plugs meet U.L. 514 flammability test.

Provide a raintight, dust and oil-tight reusable seal for electrical knockouts.

NEMA 3R, 4, 6 and 13 boxes can be saved or re-used whenever a knockout is no longer used.

No tools needed to install; just push into hole and they snap in.

General

Trade Size (inches)	1/2
---------------------	-----

Material	Neoprene
----------	----------

Dimension Information

Dimension A (inches)	1 9/32
----------------------	--------

Knockout Size (inches)	1/2
------------------------	-----

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

T&B Inner Pack	100
----------------	-----

Package in Units	1000
------------------	------

T&B Sold in UOM	Each
-----------------	------

T&B Weight Per UOM	1.25 lbs. per 100
--------------------	-------------------

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications

File Nbr:

E 13938

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com