



## Liquidtight Flexible Cord & Cable Fittings

### T&B Catalog Number:

2594

### UPC Number:

78621002594

### Status:

Active

### Description:

3 in. straight malleable iron liquidtight strain relief cord connector, cord range-2.535-2.750.

### Application

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

Meets Coast Guard CG293

### General

Material Malleable Iron

### Dimension Information

Hub Size (inches)	3
Dimension A (inches)	3 15/16
Dimension B (inches)	4 1/4
Dimension C (inches)	1 1/32
Cord Range (inches)	2.535-2.750
Throat Diameter (inches)	2 13/32

### Specifications

3dmodel	Available on Website
Temperature Rating	105 C

### Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	400 lbs. per 100

### Application Support

Product Overview	Available on Website
Specifications	Available on Website
Portable Cord Selection Table	Available on Website

### Notes

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

### Certifications

RoHS Compliance Yes

### Certifications



File Nbr:  
E 13938

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289

