

S39391

22W/LED/HID/5000K/100-277V/E26 22 watt LED HID Replacement; 5000K; Medium base; 100-277

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 2.5KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size									
Length	Width	Depth							
8.5 inch	6 inch	6 inch							

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 250V) 92-406



S39391

S393	391	Hi-Pro	045	923303913	100 - 277	22	2 5	50/60Hz 15		60W		40W	
HID Eq	uivalent	Base	e ANS Bas		Lamp Cod	de			nmable/ Dimmab		Finish	MOL Ir Inches	
100	OW	Mediu	ım E2	6 22W/LE	ED/HID/5000K/	100-27	77V/E26	No	n-Dimm	able	White	5-11/16	5" 2-3/8"
Initial L	umens	Hc	e Rated ours	Kelvin Temp	Color	CRI	Beam Sp Deg)		g Position			emperature maximum of
3080		50000		5000	Natural Light	80	300	300 Uni		iversal		+65C (+149F)	
Pack	Pack Ty	_	CEC	Status	Material		oHS npliant		or ETL sted	UL C	Classifica	tion	Warranty
48	Вс	ОХ		or sale in ornia	Aluminum	,	Yes	Υ	⁄es	cULus -	Damp Lo Rated	ocation	5 Year Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051