# **A200 Heater**

**FH79** 

**UPC:**786678670812

#### **Dimensions:**

Height: XLength: XWidth: X

**Notes:**Select heater coils based on full load current(FLA) shown on motor nameplate. Heater coils are rated to protect 40 degree C rise and a service factor of 1.15, Single-Phase requires 2 heaters, Three-Phase Requires 3 heaters

#### Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

 Special Features: Used with A200 Starter Sizes 3 &4, 3-Phase Only

Type: A200 HeaterDesign: NEMA

 Full Load Current Range: Ambient 37.6-41.5A, Non-Comp 34.6-38.2A

Overload Relay: Type A and BTrip Type: Thermal and Fast Trip

#### **Supporting documents:**

- Eatons Volume 5-Motor Control and Protection
- Instructions for A200, A210, A250 size 6, twoor three-pole non-reversing or reversing motor controllers
- Eaton Specification Sheet FH79

## **Certifications:**

- UL Listed
- CSA Certified



P	ro	duc	t co	mnli	iance:	No	Data
	ı	uuc		шрп	iaiice.	INO	Data

© 2016 Eaton. All rights reserved.