

COMMERCIAL

Three-phase - Aluminum winding - DA6 Series

Aluminum Series DA6, Type 3R Three-phase, Primary 600V, Secondary 208Y/120V, 150° C

kVA	Mounting (1)	Catalog number (2)	Dimensions (3)				Weight		Enclosure	Wiring diagram
			Height		Width		lb	kg		
			In	mm	In	mm				
15	*W/F	DA6015V	17	422	20	511	165	75	Fig 1	WD3
30	*W/F	DA6030V	23	574	22	561	285	130	Fig 2	WD3
45	*W/F	DA6045V	25	635	25	635	345	157	Fig 3	WD3
75	F	DA6075V	31	993	26	668	540	245	Fig 4	WD3
112.5	F	DA6112V	39	993	29	737	750	341	Fig 5	WD3
150	F	DA6150V	39	993	29	737	885	403	Fig 5	WD3
225	F	DA6225V	49	1229	38	960	1500	682	Fig 6	WD3
300	F	DA6300V	49	1229	38	960	1750	795	Fig 6	WD3
450	F	DA6450V	56	1422	42	1067	2400	1091	Fig 7	WD4

(1) W = Wall mount F = Floor mount

(2) Catalog number

THREE-PHASE: 15 - 300 kVA 2 x FCAN, 2 x FCBN 4 x 2.5%

(3) The dimensions are applicable for Type 3R enclosure only

All weights and dimensions are approximate and subject to change without notice.

*Wall mount brackets are optional

Aluminum Series DA6, Three-phase, Primary 480V, Secondary 208Y / 120V, 150° C

kVA	Mounting (1)	Catalog number (2)	Dimensions (3)				Weight		Enclosure	Wiring diagram
			Height		Width		lb	kg		
			In	mm	In	mm				
15	*W/F	DA6015R	17	422	20	511	165	75	Fig 1	WD3
30	*W/F	DA6030R	23	574	22	561	285	130	Fig 2	WD3
45	*W/F	DA6045R	25	635	25	635	345	157	Fig 3	WD3
75	*W/F	DA6075R	31	790	26	668	540	245	Fig 4	WD3
112.5	F	DA6112R	39	993	29	737	750	341	Fig 5	WD3
150	F	DA6150R	39	993	29	737	885	403	Fig 5	WD3
225	F	DA6225R	49	1229	38	960	1500	682	Fig 6	WD3
300	F	DA6300R	49	1229	38	960	1750	795	Fig 6	WD3

(1) W = Wall mount F = Floor mount

(2) Catalog number

THREE-PHASE: 15 - 300 kVA 2 x FCAN, 2 x FCBN 4 x 2.5%

(3) The dimensions are applicable for Type 3R enclosure only

All weights and dimensions are approximate and subject to change without notice.

*Wall mount brackets are optional