


VuLite® 6" Line Voltage Housings and Trims

IC Housings

V6IC W 6" IC New Construction
V6ICN W 6" IC New Construction with Floating Socket

Energy efficient housing.
 May be covered with insulation.


Dimensions:
 13-3/4"L x 13-3/8"W x 7-3/8"H
 Ceiling Cutout: 6-1/2" Diameter



TC Housings


V6TC W
 6" TC New Construction
 Requires 3" spacing from insulation.

Dimensions:
 13-3/4"L x 13-3/8"W x 7-3/8"H
 Ceiling Cutout: 6-1/2" Diameter




V6ICR W
 6" IC Remodel
 Energy efficient housing.
 May be covered with insulation.

Dimensions:
 13-3/4"L x 6-3/4"W x 7-3/8"H
 Ceiling Cutout: 6-1/4" Diameter



V6TCR W
 6" TC Remodel
 Requires 3" spacing from insulation.

Dimensions:
 13-3/4"L x 6-3/4"W x 7-3/8"H
 Ceiling Cutout: 6-1/4" Diameter




Accessories: **VALG6** Airloc® gasket kit for V6IC W housing when an Airloc® trim is not being used. **G2405** Set of(4) T-bar clips for installation in suspended ceilings.

6" Compatible Trims

Conical Baffle
V3024 WWH White
V3024 BWH Black


Aperture: 5-3/4"
 Outer Diameter: 7-3/4"



Juno Compatible Housings: Lamp Wattage/Type
V6IC W, V6ICR W: 50W PAR30, 75W PAR30L, 65W BR30
V6TC W, V6TCR W: 75W PAR30/PAR30L, 65W BR30, 120W BR40
IC22, IC22R: 50W PAR30, 75W PAR30L, 65W BR30
IC2, TC2, TC2R: 75W PAR30 w/socket extender, 75W PAR30L, 65W BR30

Straight Baffle
V3025 WWH White
V3025 BWH Black


Aperture: 5-3/4"
 Outer Diameter: 7-3/4"



Juno Compatible Housings: Lamp Wattage/Type
V6IC W, V6ICR W: 50W PAR30/PAR30L, 75W PAR38
V6TC W, V6TCR W: 75W PAR30/PAR30L, 65W BR30, 120W BR40, 120W PAR38
IC22, IC22R: 75W PAR30/PAR30L, 65W BR30, 75W PAR38
IC2: 75W PAR30 w/socket extender, 75W PAR30L, 65W BR30, 90W PAR38, 100W BR40
TC2, TC2R: 75W PAR30 w/socket extender, 75W PAR30L, 65W BR30, 150W PAR38, 120W BR40

Full Baffle
V3034 WWH White
V3034 BWH Black
V3034T WWH White w/Torsion Springs
V3034T BWH Black w/Torsion Springs

Aperture: 5-3/4"
 Outer Diameter: 7-5/8"



Juno Compatible Housings: Lamp Wattage/Type
V6IC W, V6ICN W, V6ICR W: 40W A19*, 75W PAR30/PAR30L, 65W BR30, 90W BR40, 90W PAR38*
V6TC W, V6TCR W: 60W A19*, 75W PAR30/PAR30L, 85W BR30, 120W BR40, 150W PAR38*
IC22, IC22R, IC23: 40W A19, 75W PAR30/PAR30L, 65W BR30, 90W BR40, 90W PAR38
IC2: 60W A19, 75W PAR30/PAR30L, 85W BR30, 100W PAR38, 120W BR40
TC2, TC2R: 60W A19, 75W PAR30/PAR30L, 85W BR30, 150W PAR38, 120W BR40
ICPL6 Series: 32W max. CFL†
PL6 Series: 42W max CFL†

* No A19 listing and 75W PAR38 max. for the V3034B Series
 † Note: For best performance, 26W is recommended.

Patent Pending

Clear Cone
V3027C WH: Clear

Aperture: 5-3/4"
 Outer Diameter: 7-3/4"



Juno Compatible Housings: Lamp Wattage/Type
V6IC W, V6ICR W: 50W PAR30, 75W PAR30L, 65W BR30
V6TC W, V6TCR W: 75W PAR30/PAR30L, 65W BR30, 90W BR40
IC2, IC22, IC22R: 50W PAR30, 75W PAR30L, 65W BR30
TC2, TC2R: 75W PAR30/PAR30L, 65W BR30