



## Mighty-Rite® Steel Split Grounding Bushings

Install your bushings before or after pulling wire and making connections. Mighty-Rite's innovative hinged design adjusts and aligns easier – even in tight spots. Our adjustable lay-in lugs accept and position conductors for simple access. Mighty-Rite's unique split design and ease-of-use allows shorter facility downtime when upgrading existing power and data systems.

cULus File No. E20412

### Steel / Aluminum Alloy Lug

Catalog Number	Grounding Lug Wire Capacity		Trade Size	Unit Qty.	Std. Pkg. Qty.
	Min. Solid	Max. Strand			
SGBS-381CL	14	4	1/2"	25	250
SGBS-382CL	14	4	3/4"	25	250
SGBS-383CL	14	4	1"	25	250
SGBS-38414	14	4	1 1/4"	20	200
SGBS-384CL	14	1/0	1 1/4"	20	200
SGBS-38514	14	4	1 1/2"	20	200
SGBS-385CL	14	1/0	1 1/2"	20	200
SGBS-38614	14	4	2"	10	100
SGBS-386CL	14	1/0	2"	10	100
SGBS-38740	6	250 MCM	2 1/2"	---	25
SGBS-387CL	14	1/0	2 1/2"	---	25
SGBS-38840	6	250 MCM	3"	---	25
SGBS-388CL	14	1/0	3"	---	25
SGBS-38940	6	250 MCM	3 1/2"	---	25
SGBS-389CL	6	3/0	3 1/2"	---	25
SGBS-39040	6	250 MCM	4"	---	20
SGBS-390CL	6	3/0	4"	---	20
SGBS-39050	350	500MCM	4"	---	10
SGBS-39150	350	500MCM	5"	---	10
SGBS-39250	350	500MCM	6"	---	10

**LOOK FOR  
BRIDGEPORT ORANGE**



**FOR PRODUCT INFORMATION ON DEMAND  
VISIT: [YOUTUBE.COM/BRIDGEPORTFITTINGS](https://www.youtube.com/bridgeportfittings)**

**SEE THE DIFFERENCE  
ORANGE MAKES™**

# **MIGHTY-RITE® NONMETALLIC SPLIT BUSHINGS**



**SB SERIES**

## **WHAT MAKES IT DIFFERENT? DOES MORE THAN JUST PROTECT CONDUCTORS.**

- No more burning through bushings or fighting with pullers
- Can be installed before or after pulling wire
- Self-aligning latch provides a simple, one-handed install
- cULus Listed
- Patented

FOR MORE INFORMATION, VISIT:  
**[WWW.BPTFITTINGS.COM](http://WWW.BPTFITTINGS.COM)**



## Mighty-Rite® Nonmetallic Split Bushings

Patented split design allows for installation after conductors have been pulled. Used with a locknut to terminate threaded rigid and IMC to a box or enclosure. Used with a connector to prevent damage to wire insulation. Rated 105°C.

cULus File No. E9391

### Nonmetallic Split Bushing

Catalog Number	Trade Size	Unit Qty.	Std. Pkg. Qty.
SB-383NM	1"	25	250
SB-384NM	1 1/4"	20	200
SB-385NM	1 1/2"	20	200
SB-386NM	2"	10	100
SB-387NM	2 1/2"	---	25
SB-388NM	3"	---	25
SB-389NM	3 1/2"	---	25
SB-390NM	4"	---	20

**LOOK FOR  
BRIDGEPORT ORANGE**



**FOR PRODUCT INFORMATION ON DEMAND  
VISIT: [YOUTUBE.COM/BRIDGEPORTFITTINGS](https://www.youtube.com/bridgeportfittings)**