

Order code	Description	Watts (W)	Base	Volts (V)	Lumens at 120 V (lm)	Average life (hrs)	Filament type	Finish	Case qty (inner/master)
G16.5 (cont.)									
MOL : 2 7/8 in. (73 mm) LCL : 2 1/16 in. (52 mm)									
50779	25G16.5/WH/3M/E14/130V/STD	25	E14	130	150	3 000	CC-6	White	25/500
50778	40G16.5/CL/3M/E14/130V/STD	40	E14	130	315	3 000	CC-6	Clear	25/500
50782	60G16.5/WH/3M/E14/130V/STD	60	E14	130	580	3 000	CC-6	White	25/500
G25									
MOL : 2 1/2 in. (114 mm) LCL : 3 1/32 in. (77 mm)									
50199	25G25/CL/3M/130V/STD	25	E26	130	135	3 000	C-9	Clear	6/60
50196	25G25/WH/3M/130V/STD	25	E26	130	115	3 000	C-9	White	6/60
50222	40G25/CL/3M/130V/STD	40	E26	130	255	3 000	C-9	Clear	6/60
50155	40G25/WH/3M/130V/STD	40	E26	130	230	3 000	C-9	White	6/60
G30									
MOL : 5 13/32 in. (137 mm) LCL : 3 9/32 in. (83 mm)									
50203	25G30/CL/3M/130V/STD	25	E26	130	115	3 000	C-9	Clear	6/60
50204	40G30/CL/3M/130V/STD	40	E26	130	230	3 000	C-9	Clear	6/60
50202	40G30/WH/3M/130V/STD	40	E26	130	215	3 000	C-9	White	6/60
G40									
MOL : 6 15/16 in. (176 mm) LCL : 3 29/32 in. (99 mm)									
50205	25G40/CL/3M/130V/STD	25	E26	130	100	3 000	C-9	Clear	6/12
50209	25G40/WH/3M/130V/STD	25	E26	130	100	3 000	C-9	White	6/12
50206	40G40/CL/3M/130V/STD	40	E26	130	230	3 000	C-9	Clear	6/12
50150	40G40/WH/3M/130V/STD	40	E26	130	215	3 000	C-9	White	6/12
50111	60G40/CL/3M/130V/STD	60	E26	130	465	3 000	C-9	Clear	6/12
50158	60G40/WH/3M/130V/STD	60	E26	130	365	3 000	C-9	White	6/12
50207	100G40/CL/3M/130V/STD	100	E26	130	760	3 000	C-9	Clear	6/12
50210	100G40/WH/3M/130V/STD	100	E26	130	820	3 000	C-9	White	6/12
50208	150G40/CL/3M/130V/STD	150	E26	130	1 175	3 000	C-9	Clear	6/12
50112	150G40/WH/3M/130V/STD	150	E26	130	1 175	3 000	C-9	White	6/12
PS25									
MOL : 6 15/16 in. (176 mm) LCL : 5 1/32 in. (128 mm)									
50140	150PS25/CL/5M/130V/STD	150	E26	130	1 210	5 000	C-9	Clear	6/24
50071	300PS25/CL/5M/130V/STD	300	E26	130	2 725	5 000	C-9	Clear	6/24
50088	300PS25/F/5M/130V/STD	300	E26	130	2 725	5 000	C-9	Frost	6/24
PS30									
MOL : 8 1/16 in. (204 mm) LCL : 5 13/32 in. (137 mm)									
52428	300PS30/CL/120V/STD	300	E26	120	3 600	5 000	C-9	Clear	6/24
51122	300PS30/F/5M/130V/STD	300	E26	130	2 725	5 000	C-9	Frost	6/24
PS35									
MOL : 9 13/32 in. (239 mm) LCL : 6 1/2 in. (165 mm)									
50225	300PS35/CL/5M/E39/130V/STD	300	E39	130	2 725	5 000	C-9	Clear	6/24
50226	300PS35/F/5M/E39/130V/STD	300	E39	130	2 725	5 000	C-9	Frost	6/24
50227	500PS35/CL/5M/E39/130V/STD	500	E39	130	6 055	5 000	C-9	Clear	6/24
50228	500PS35/F/5M/E39/130V/STD	500	E39	130	6 055	5 000	C-9	Frost	6/24
R14									
MOL : 2 1/8 in. (54 mm) LCL : 1 21/32 in. (42 mm)									
50665	25R14/FL/1.5M/120V/STD	25	E26	120	150	1 500	CC-2V	Clear	6/120
50663	40R14/CL/FL/1.5M/120V/STD	40	E26	120	280	1 500	CC-2V	Clear	6/120
MOL : 2 9/16 in. (65 mm) LCL : 1 31/32 in. (50 mm)									
50666	25R14/FL/1.5M/E17/120V/STD	25	E17	120	150	1 500	CC-2V	Clear	6/120
R16									
MOL : 3 1/2 in. (89 mm)									
52168	25R16/SF/1.5M/E12/130V/STD	25	E12	130	120	3 000	CC-2V	Frost	25/500
R19									
MOL : 3 31/32 in. (101 mm) LCL : 3 1/32 in. (77 mm)									
50136	40R19/SW/1.5M/120V/STD	40	E26	120	320	1 500	CC-6	Soft white	6/60
50138 ¹	75R19/SW/1.5M/120V/STD	75	E26	120	770	1 500	CC-6	Soft white	6/60
R20									
MOL : 3 29/32 in. (99 mm) LCL : 2 15/16 in. (75 mm)									
50211	30R20/SP/5M/130V/STD	30	E26	130	145	5 000	C-9	Clear	6/60
50215	30R20/FL/5M/130V/STD	30	E26	130	130	5 000	C-9	Frost	6/60
61703	45R20/FL/5M/130V/STD	45	E26	130	255	5 000	CC-6	Frost	6/60
61705	45R20/SP/5M/130V/STD	45	E26	130	255	5 000	CC-6	Frost	6/60
50213 ¹	75R20/SP/5M/130V/STD	75	E26	130	575	5 000	CC-6	Clear	6/60

¹This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.