

T100 Series 24-Hour Mechanical Time Switches in Enclosure



- Highest motor load ratings in the industry
- 12 ON/OFF operations per day
- ON/OFF trippers included
- Available with pool heater protection

Without Pool Heater Protection

Model #	Enclosure	Switch	Input Voltage
T101P3	Type 3R Plastic	SPST	120 VAC, 60 Hz
C. T104P3	Type 3R Plastic	DPST	208-277 VAC, 60 Hz
T106P3	Type 3R Plastic	1 N.O./1 N.C.	208-277 VAC, 60 Hz
D. T101R3	Type 3R Steel	SPST	120 VAC, 60 Hz
T104R3	Type 3R Steel	DPST	208-277 VAC, 60 Hz

With Pool Heater Protection

Model #	Enclosure	Switch	Input Voltage
T101P201	Type 3R Plastic	SPST	120 VAC, 60 Hz
T104P201	Type 3R Plastic	DPST	208-277 VAC, 60 Hz
E. T101R201	Type 3R Steel	SPST	120 VAC, 60 Hz
T104R201	Type 3R Steel	DPST	208-277 VAC, 60 Hz

Rating:

Switch Rating:

- 40 A Resistive each pole, 120-480 VAC
- 40 A Tungsten, Inductive or 1000 VA Pilot Duty each pole 120-277 VAC
- 2 HP (24 FLA) 120 VAC
- 5 HP (28 FLA) 240 VAC

Heater Control Circuit: 10 A, 240 VAC max.

Operating Temperature Range: -40°F to 130°F (-40°C to 54°C)

Warranty: 1 year

For replacement parts, trippers and accessories, see page 153.
For additional enclosures, see page 146.



C.



D.



E.