


LED PAR30

800 Lumen 10 Watt 3000K PAR30 Short Neck 40°




PRODUCT DESCRIPTION

10 watt PAR30 EarthBulb LED floodlight replaces 75 watt incandescent floodlights for over 85% energy savings. Great for use in dimming recessed lighting, track lighting and display lighting applications. High power LED and an advanced cooling system provides for 15,000 hours of LED life. Medium screw base. Suitable for outdoor use, damp location rated. Energy Star rated product.

PRODUCT FEATURES

- Dimming PAR30 short neck flood light provides 800 lumens, capable of than 9% dimming to less
- This Energy Star product provides 40° beam angle
- Unique LED array design look like halogen when powered on
- Chipset provides 3000K white light with a high color rendering rating over 80
- Wet rated UL and suitable for exterior locations
- Face of the lamp looks like standard PAR lamps
- Fits track heads like a PAR lamp is intended

PRODUCT APPLICATIONS




LUMINOUS DISTRIBUTION INTENSITY DATA

Intensity (Candlepower) Summary at 25°C - Candelaes

V \ H(°)	0	22.5	45	67.5	90
0	1916	1916	1916	1916	1916
5	1858	1835	1816	1803	1791
10	1645	1601	1567	1542	1515
15	1279	1217	1178	1146	1111
20	837.6	784.8	754.3	723.2	689.9
25	475.3	437.9	422.7	400.4	376.2
30	248.6	229.5	219.9	210.2	194.7
35	133.5	123.7	119.3	113.6	106.2
40	78.3	73.6	71.3	68.8	64.9
45	52.6	50.1	48.7	47.3	45.2
50	38.8	37.5	36.7	35.6	34.4
55	30.2	29.4	28.8	27.9	27.3
60	23.9	23.3	22.8	22.0	21.6
65	18.6	18.1	17.6	17.0	16.6
70	14.0	13.5	13.2	12.7	12.4
75	10.1	9.6	9.4	9.0	8.7
80	6.8	6.4	6.3	6.0	5.8
85	4.4	4.1	3.9	3.7	3.6
90	2.4	2.2	2.1	2.0	1.9


LUMINOUS DISTRIBUTION INTENSITY DIAGRAM



MODEL NUMBER: LP31230DSN7

ORDER CODE: 10823

Order Code	Individual UPC	Master Park UPC	Qty
10823	840791108239	84079110823900	12
Dimensions (inches - Length x Width x Height)			
10823	3.93 x 3.93 x 3.85		12
Weight (lbs)			
10823	.407	6.05	12



Electrical	
Watt	10
Power Factor	> 0.8
Voltage	120 volt
Frequency	60Hz
Base Type	E26 Medium
Operating Temperature Range	-4F to 104F
Light	
Initial Lumens	800
Lumens per Watt	80
Color Temperature	3000K
Color Rendering (CRI)	83
Beam Angle	40°
Agency Approvals	
UL	Yes
Energy Star	15,000 hours
RoHS	Yes
FCC	Yes
Product Details	
Warranty	10 years 6 hr/day
Diameter	3.63"
Nominal Length	3.31"

