

PS20AC1LA

Readily installed in the plant or at the office — you can rely on all of our switches for years of quiet, trouble-free operation.


HP Conversion Table – Switches

15 Amp	1/2 Horsepower at 120VAC 2 Horsepower at 240VAC
20 Amp	1 Horsepower at 120VAC 2 Horsepower at 240VAC
30 Amp	2 Horsepower at 120VAC 2 Horsepower at 240VAC


Index

Device	Rating	Page Number
Horsepower Rating Chart		A-1
Industrial Extra Heavy-Duty Spec Grade Switches	15, 20 & 30A, 120, 277 & 120/277VAC	A-2
Lock Switch Keys		A-2
Extra Heavy-Duty Spec Grade & Security Switches Hard Use & Commercial	15 & 20A, 347VAC; 20A, 120/277VAC	A-3
Specification Grade Switches	15 & 20A, 120/277VAC	A-4
Manual Controllers	30 & 40A, 1ø & 3ø; 15, 20 & 30A, 120/277VAC; 60A NEMA 3R; 20 & 30A, 1ø	A-5 – A-9
TradeMaster® Grounding Toggle Switches	15A, 120VAC	A-10, A-11
TradeMaster® Non-Grounding Toggle Switches	15A, 120VAC	A-12
Combination Switches	15 & 20A, 120/277VAC; 15A, 120/125VAC; 20A, 120VAC	A-13, A-14
Specification Grade Decorator Switches	15 & 20A, 120/277 & 347VAC; 20A, 120VAC	A-15
TradeMaster® Decorator Switches	15A, 120 & 120/277VAC	A-16, A-17
Momentary & Maintained Contact Switches	15A, 120 & 120/277VAC	A-18
Spec Grade Decorator Combination Switches	20A, 277VAC	A-19
Shim-Lock		A-19
TradeMaster® Decorator Combination Switches	15A, 120/125 & 120/277VAC	A-20 – A-22
Decorator Combination Tamper-Resistant Switch/GFCI	15A, 125VAC	A-23
Canopy Switches & Locator Switches	15A, 120 & 250VAC; 15A, 120VAC	A-24


Pass & Seymour



15 & 20 Amp*



15 & 20 Amp Lighted & Pilot Lighted*



Locking*

*30AC series is 1.437" wide

Lock Switch Replacement Keys

(One key furnished with each switch)



500K

Fits new Switches



1498

Fits Switches manufactured before 1976



1498-NT

Fits Switches manufactured 1976-present

All devices listed on this page conform to NEMA WD-1 and WD-6.

Switches

Industrial Extra Heavy-Duty Specification Grade Switches

15, 20 & 30A, 120, 277 & 120/277VAC

Features

- External screw-pressure-plate back and side wired. Accepts #14 – #10 AWG copper or copper-clad conductors.
- Heavy-gauge one-piece copper alloy contact arm virtually eliminates contact bounce.
- Cam controls fast “make” and positive “break” to minimize arcing.
- Heavy-duty bumper pads for quiet operation.
- High strength thermoplastic polycarbonate toggle.
- Back body made of glass-reinforced nylon.
- Locking support provides resistance to face and back body separation.
- Oversized silver alloy contacts for long life and better heat dissipation.
- Grounding terminal is standard.
- Shallow design for ease of installation.
- Strap nickel-plated steel with integral ground.
- Auto-ground clip assures positive ground.

Catalog Number				Rating	Color	3rd Party Compliance		
Single Pole	Double Pole	Three-Way	Four-Way	A. VAC		UL	FSUL	CS
						UL20 WS896 C22.2 111		
Toggle Switches Back & Side Wire								
PS15AC1I	PS15AC2I	PS15AC3I	PS15AC4I	15 120/277	Ivory	•	•	•
PS15AC1W	PS15AC2W	PS15AC3W	PS15AC4W	15 120/277	White	•	•	•
PS15AC1	PS15AC2	PS15AC3	PS15AC4	15 120/277	Brown	•	•	•
PS15AC1GRY	PS15AC2GRY	PS15AC3GRY	PS15AC4GRY	15 120/277	Gray	•	•	•
PS15AC1LA	PS15AC2LA	PS15AC3LA	PS15AC4LA	15 120/277	Light Almond	•	•	•
PS20AC1I	PS20AC2I	PS20AC3I	PS20AC4I	20 120/277	Ivory	•	•	•
PS20AC1W	PS20AC2W	PS20AC3W	PS20AC4W	20 120/277	White	•	•	•
PS20AC1	PS20AC2	PS20AC3	PS20AC4	20 120/277	Brown	•	•	•
PS20AC1GRY	PS20AC2GRY	PS20AC3GRY	PS20AC4GRY	20 120/277	Gray	•	•	•
PS20AC1BK	PS20AC2BK	PS20AC3BK	PS20AC4BK	20 120/277	Black	•	•	•
PS20AC1RED	PS20AC2RED	PS20AC3RED	PS20AC4RED	20 120/277	Red	•	•	•
PS20AC1LA	PS20AC2LA	PS20AC3LA	PS20AC4LA	20 120/277	Light Almond	•	•	•
PS30AC1I	PS30AC2I	PS30AC3I		30 120/277	Ivory	•	•	•
PS30AC1W	PS30AC2W			30 120/277	White	•	•	•
PS30AC1	PS30AC2	PS30AC3		30 120/277	Brown	•	•	•
Lighted Toggle Switches (Lighted when OFF) Back & Side Wire								
PS15AC1CSL		PS15AC3CSL		15 120/277	Clear	•	•	•
PS15AC1ISL		PS15AC3ISL		15 120/277	Ivory	•	•	•
PS15AC1WSL		PS15AC3WSL		15 120/277	White	•	•	•
PS20AC1CSL		PS20AC3CSL		20 120/277	Clear	•	•	•
PS20AC1ISL		PS20AC3ISL		20 120/277	Ivory	•	•	•
PS20AC1WSL		PS20AC3WSL		20 120/277	White	•	•	•
PS20AC1LASL		PS20AC3LASL		20 120/277	Light Almond	•	•	•
Pilot Lighted Switches (Lighted when ON) Back & Side Wire								
PS15AC1CPL		PS15AC3CPL		15 120	Clear	•	•	•
PS15AC1RPL		PS15AC3RPL		15 120	Red	•	•	•
PS20AC1CPL		PS20AC3CPL		20 120	Clear	•	•	•
PS20AC1CPL7				20 277	Clear	•	•	•
PS20AC1RPL		PS20AC3RPL		20 120	Red	•	•	•
PS20AC1RPL7		PS20AC3RPL7		20 277	Red	•	•	•
	PS20AC2CPL			20 120/277	Clear	•	•	•
	PS20AC2RPL			20 120/277	Red	•	•	•
PS30AC1RPL		PS30AC3RPL		30 120	Red	•	•	•
	PS30AC2RPL			30 120/277	Red	•	•	•
Lock Switches (Key can be removed in both positions) Back & Side Wire								
PS15AC1L		PS15AC3L		15 120/277	Gray	•	•	•
PS20AC1IL	PS20AC2IL	PS20AC3IL	PS20AC4IL	20 120/277	Ivory	•	•	•
PS20AC1WL	PS20AC2WL	PS20AC3WL	PS20AC4WL	20 120/277	White	•	•	•
PS20AC1L	PS20AC2L	PS20AC3L	PS20AC4L	20 120/277	Gray	•	•	•
PS20AC1REDL	PS20AC2REDL	PS20AC3REDL	PS20AC4REDL	20 120/277	Red	•	•	•
PS20AC1LAL	PS20AC2LAL	PS20AC3LAL	PS20AC4LAL	20 120/277	Light Almond	•	•	•


Switches Extra Heavy-Duty Specification Grade & Security Switches

15 & 20A, 347VAC; 20A, 120/277VAC

Pass & Seymour



Features	
<ul style="list-style-type: none"> ■ External screw-pressure-plate back and side wired. Accepts #14 – #10 AWG copper or copper-clad conductors. ■ Heavy-gauge one-piece copper alloy contact arm virtually eliminates contact bounce. ■ Cam controls fast “make” and positive “break” to minimize arcing. ■ Heavy-duty bumper pads for quiet operation. ■ High strength thermoplastic polycarbonate toggle. 	<ul style="list-style-type: none"> ■ Back body made of glass-reinforced nylon. ■ Locking support provides resistance to face and back body separation. ■ Oversized silver alloy contacts for long life and better heat dissipation. ■ Grounding terminal is standard. ■ Shallow design for ease of installation. ■ Strap nickel-plated steel with integral ground. ■ Auto-ground clip assures positive ground.




**15 & 20 Amp
Canadian 347VAC**

Catalog Number		Rating A. VAC	Color	3rd Party Compliance	
Single Pole	Three-Way			UL	SP
347VAC Toggle Switches Back & Side Wire					
☸ PS371510I	☸ PS371530I	15 347	Ivory		•
☸ PS371510W	☸ PS371530W	15 347	White		•
☸ PS371510	☸ PS371530	15 347	Brown		•
☸ PS371510GRY	☸ PS371530GRY	15 347	Gray		•
☸ PS371510BK	☸ PS371530BK	15 347	Black		•
☸ PS371510RED	☸ PS371530RED	15 347	Red		•
☸ PS372010I	☸ PS372030I	20 347	Ivory		•
☸ PS372010W	☸ PS372030W	20 347	White		•
☸ PS372010	☸ PS372030	20 347	Brown		•
☸ PS372010GRY	☸ PS372030GRY	20 347	Gray		•
☸ PS372010BK	☸ PS372030BK	20 347	Black		•
☸ PS372010RED	☸ PS372030RED	20 347	Red		•
☸ PS372010LA	☸ PS372030LA	20 347	Light Almond		•
☸ PS372010L	☸ PS372030L	20 347	Gray, Locking		•
☸ Denotes Canadian catalog number. All Canadian products have Combination Slotted/Robertson Head Brass Screws.					

Features	
<ul style="list-style-type: none"> ■ Back and side wired. Accepts #14 – #10 AWG. ■ Operated by cam lock for maximum security in critical areas. ■ Recommended for tamper-proof installation in schools, public housing, trailer parks, freight yards, etc. 	<ul style="list-style-type: none"> ■ Uses same key as Cat.# 4600 cast enclosure. ■ Key can be removed in both positions.

Catalog Number				Rating A. VAC	3rd Party Compliance		
Single Pole	Double Pole	Three-Way	Four-Way		UL	FSUL	SP
Security Switches Back & Side Wire							
PS20AC1KL	PS20AC2KL	PS20AC3KL	PS20AC4KL	20 120/277	•	•	•
☸ PS372010KL		☸ PS372030KL		20 347	•		•
☸ Denotes Canadian catalog number. All Canadian products have Combination Slotted/Robertson Head Brass Screws.							



Security Switch

Stainless Steel Plate for PS20AC-KL Switches Single Gang – SS717, Double Gang – SS727.

For custom combinations specify opening Style No. 302.

Catalog Number 4609 Security Switch Replacement Keys for PS20ACKL Switches (2 keys furnished with each switch).

All devices listed on this page conform to NEMA WD-1 and WD-6.