

## Eaton M-Max Series sensorless vector adjustable frequency drive

**MMX11AA2D8N0-0**

**UPC:**786685268460

### Dimensions:

- **Height:** 4 IN
- **Length:** 3.54 IN
- **Width:** 7.68 IN

**Weight:**1.54 LB

**Notes:**Horsepower ratings are based on the use of a 240V, 460V, and 575V NEMA B, four- or six-pole squirrel cage induction motor and are for reference only.

### Warranties:

- 2 year

### Specifications:

- **Input Current:** 12.4 A
- **Output Current:** 2.8 A
- **Frame Size:** FR2
- **Horsepower:** 0.75 hp
- **Phase:** Single-phase in, three-phase out
- **Rating:** IP20
- **Special Features:** AA software design series
- **Type:** Full version
- **Voltage Rating:** 100-120 V, 230 V

### Supporting documents:

- [Variable frequency drive - Product overview](#)
- [Eatons Volume 6-Solid-State Motor Control](#)
- [MMX\\_\(FR2\) 2D Drawing Xchange](#)
- [MMX\\_\(FR2\) AutoCAD 2D Footprint](#)
- [MMX\\_\(FR2\) 3D Inventor](#)
- [MMX\\_\(FR2\) AutoCAD 2D Footprint \(mm\)](#)
- [MMX\\_\(FR2\) 3D Model Xchange](#)



- [MMX\\_\(FR2\) 2D PDF](#)
- [User Manual, M-Max Series Adjustable Frequency Drive](#)
- [M-Max Series adjustable frequency drives](#)
- [Eaton Specification Sheet - MMX11AA2D8N0-0](#)

**Certifications:**

- EN 60204-1
- EN 61800-5-1
- UL Listed
- EN 61800-3
- cUL Certified

**Product compliance:**

- RoHS Compliant
- CE Marked
- EMC Category C2, C3, and C4 (Level H): With an internal RFI filter option
- C-Tick Compliant