TI073-3W-B/U

7-Day programmable wall switch with solar timetable for lights, white

Product Info | Literature

Product Specifications

Application	Halogen lights; Fluorescent lights; Incadescent lights
Dimensions (in.)	1-13/16 in. wide x 2-23/32 in. high x 1-13/16 in. deep
Dimensions (mm)	43 mm wide x 68 mm high x 43 mm deep
Comments	Single pole 2-wire or multiswitch (3-way) 3 wire; White backlit screen; Hidden lock
Electrical Ratings	Maximum Load--500 W @ 120 V, 40 W min.; Resistive Load--40 W min., 500 W max. @ 120 Vac
Frequency	60 Hz
Approvals, Underwriters Laboratories Inc.	Approved
Electrical Connections	Multiswitch (3-way), 3 wire; Single pole 2 wire
Voltage	120 Vac
Shipping and Storage Temperature Range (F)	-40 F to 140 F
Shipping and Storage Temperature Range (C)	-40 C to 60 C
Approvals, Canadian Underwriters Laboratories Inc.	Approved
Ambient Temperature Range (F)	Operating: 5 F to 122 F
Ambient Temperature Range (C)	Operating: -15 C to 50 C
Programmability	Weekly/Daily Programming (21 on, 21 off); Solar timetable; Random
Operating Mode	Random; Manual (conventional on/off switch); Automatic