


TYPE ILSCONS

Features

- Spade configuration
- Funnel wire entry
- Vinyl insulation
- Color coded
- Manufactured from high strength copper alloy
- Electro-tin plated
- Brazed barrel
- UL Listed for 600 volts, 75° C

Benefits

- Same benefit as fork configuration, but with the added benefit of sides that are able to lie flat against barrier portion of terminal blocks
- Smooth wire insertion into barrel
- Provides corrosion resistance and strain relief
- Provide easy wire range identification
 - #18-22 AWG Red
 - #14-16 AWG Blue
 - #10-12 AWG Yellow
- Offers maximum conductivity
- Provides low contact resistance
- Stronger crimp connection that will not split open, prevents wire pull out
- Ensures reliability for copper conductor



Catalog Number	Wire Range	Stud Size	Dimensions - in. (mm)			Installation Tool ILST-22K	Package Quantity	
			L		W			
VSBR-18-4-P50	18-22	4	0.827	(21.0)	0.224	(5.7)	Die Set A	50
VSBR-18-6-P50	18-22	6	0.827	(21.0)	0.283	(7.2)	Die Set A	50
VSBR-18-8-P50	18-22	8	0.827	(21.0)	0.319	(8.1)	Die Set A	50
VSBR-18-10-P50	18-22	10	0.827	(21.0)	0.374	(9.5)	Die Set A	50
VSBR-18-14-P50	18-22	1/4	1.063	(27.0)	0.472	(12.0)	Die Set A	50
VSBR-14-6-P50	14-16	6	0.827	(21.0)	0.283	(7.2)	Die Set A	50
VSBR-14-8-P50	14-16	8	0.827	(21.0)	0.311	(7.9)	Die Set A	50
VSBR-14-10-P50	14-16	10	0.827	(21.0)	0.366	(9.3)	Die Set A	50
VSBR-14-14-P50	14-16	1/4	1.063	(27.0)	0.472	(12.0)	Die Set A	50
VSBR-10-6-P25	10-12	6	1.004	(25.5)	0.327	(8.3)	Die Set A	25
VSBR-10-8-P25	10-12	8	1.004	(25.5)	0.327	(8.3)	Die Set A	25
VSBR-10-10-P25	10-12	10	1.004	(25.5)	0.354	(9.0)	Die Set A	25
VSBR-10-14-P25	10-12	1/4	1.240	(31.5)	0.472	(12.0)	Die Set A	25
VSBR-10-516-P25	10-12	5	1.201	(30.5)	0.551	(14.0)	Die Set A	25

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
Tested to UL 486A/B, UL File E6207