

Replacement Classic Circuit Breakers

Bolt-On Type BQL Single, Multi-Pole, Duplex™, & Quadplex™

Type BQL ②

- ◆ 10,000 / 22,000 Amperes Interrupting Capacity at 120/240VAC.
- ◆ Captive line screw included (#2 Robertson/Slot).

Product Selection

Table 77. Single and Multi-Pole Bolt-On Classic Replacement Circuit Breakers

Ampere Rating	Wire Size Range (Cu/AL 60°C or 75°C) (AWG)	1-Pole 120/240VAC	1-Pole 120/240VAC	2-Pole 120/240VAC	3-Pole 120/240VAC	3-Pole 120/240VAC	
		10kAIC Catalogue Number	22kAIC Catalogue Number	10kAIC Catalogue Number	10kAIC Catalogue Number	22kAIC Catalogue Number	
15	#14 - 8	BQL15 ①	HBQL15	BQL215	BQL315	HBQL315	
20	#14 - 8	BQL20 ①	HBQL20	BQL220	BQL320	—	
25	#14 - 8	BQL25	HBQL25	BQL225	—	—	
30	#14 - 8	BQL30	HBQL30	BQL230	BQL330	HBQL330	
40	#14 - 4	BQL40	HBQL40	BQL240	BQL340	—	
50	#14 - 4	BQL50	HBQL50	BQL250	BQL350	HBQL350	
60	#8 - 2/0	BQL60	HBQL60	BQL260	BQL360	HBQL360	
70	#8 - 2/0	—	—	BQL270	BQL370	HBQL370	
90	#8 - 2/0	—	—	BQL290	BQL390	HBQL390	
100	#8 - 2/0	—	—	BQL2100	BQL3100	HBQL3100	
125	#8 - 2/0	—	—	BQL2125	—	—	
135	#8 - 2/0	—	—	BQL2135	—	—	
Requires One 1-Inch (25.4mm) Space				Requires Two 1-Inch (25.4mm) Spaces		Requires Three 1-Inch (25.4mm) Spaces	

Type BQL Duplex™ and Quadplex™ ②

- ◆ 10,000 Amperes Interrupting Capacity at 120/240VAC.
- ◆ Captive line screw included (#2 Robertson/Slot).

Product Selection

Table 78. Type BQL Duplex™ and Quadplex™ Bolt-On Classic Replacement Circuit Breakers

Duplex™		Quadplex™ Independent Trip			Quadplex™ Independent Trip					
Two Single Pole Circuits		Two Single Pole Circuits and One Double Pole Circuit			Two Double Pole Circuits					
120VAC		120VAC		120/240VAC		120VAC		120/240VAC		Wire Size Range (Cu/AL 60°C or 75°C) (AWG)
Ampere Rating	Catalogue Number	Ampere Rating	Ampere Rating	Ampere Rating	Ampere Rating	Ampere Rating	Ampere Rating	Ampere Rating	Ampere Rating	
Ampere Rating	Catalogue Number	Outer Left (1 Pole)	Centre (2 Poles)	Outer Right (1 Pole)	Catalogue Number	Outer Left & Right (2 Poles)	Centre (2 Poles)	Catalogue Number	Catalogue Number	
15-15	BQLT-15 ①	15	15	15	BQLT-15-215	15	15	BQLT-215-215	BQLT-215-215	#14 - 4
20-20	BQLT-20 ①	15	20	15	BQLT-15-220	20	20	BQLT-220-220	BQLT-220-220	#14 - 4
30-30	BQLT-30 ①	15	25	15	BQLT-15-225	15	30	BQLT-215-230	BQLT-215-230	#14 - 4
—	—	15	30	15	BQLT-15-230	15	40	BQLT-215-240	BQLT-215-240	#14 - 4
—	—	15	40	15	BQLT-15-240	—	—	—	—	#14 - 4
Requires One 1-Inch (25.4mm) Space		Requires Two 1-Inch (25.4mm) Spaces			Requires Two 1-Inch (25.4mm) Spaces					

① Switching duty rated (SWD).

② HACR rated.

③ Internal common trip.