

GENERAL PURPOSE TRANSFORMERS

Single-phase - Aluminum winding- CD2A Series

Aluminum Series CD2A, Single-phase, Type 3R, Primary 600V or 480V, 115° C

kVA	Mounting (1)	Catalog number (2)	Dimensions						Weight		Noise Level
			Height		Width		Depth		lb	kg	dB
			In	mm	In	mm	In	mm			
15	W/F	CD2A0015**B6XXLD	33	838	21	533	16	406	216	98	50
25	W/F	CD2A0025**B6XXLD	33	838	21	533	16	406	267	121	50
37.5	W/F	CD2A0037**B6XXLD	33	838	21	533	16	406	337	153	50
50	F	CD2A0050**B6XXLD	47	1194	24	610	23	584	472	214	50
75	F	CD2A0075**B6XXLD	47	1194	24	640	23	584	613	278	55
100	F	CD2A0100**B6XXLD	51	1295	28	711	27	656	813	369	55
150	F	CD2A0150**B6XXLD	58	1473	32	813	30	762	1038	471	60
200	F	CD2A0200**B6XXLD	58	1473	32	813	30	762	1195	542	65
250	F	CD2A0250**B6XXLD	Consult our Customer Service								

(1) W = Wall mount F = Floor mount
 (2) Catalog number

SINGLE-PHASE: 15 - 250 kVA 2 x FCAN, 2 x FCBN 4 x 2.5%

STANDARD VOLTAGE
 **(VK) 600 - 240/120 **(RK) 480- 240/120

All weights and dimensions are approximate and subject to change without notice.
 For the electrical schematic diagrams see Section 7, page 20

GENERAL PURPOSE TRANSFORMERS

Three-phase - Aluminum winding - CD6A Series

Aluminum Series CD6A, Three-phase, Type 3R, Primary 600V or 480V, 150° C

kVA	Mounting (1)	Catalog number (2)	Dimensions						Weight		Noise Level
			Height		Width		Depth		lb	kg	
			In	mm	In	mm	In	mm			
15	W/F	CD6A0015**A6XXBD	26	660	18	464	15	375	207	94	45
30	W/F	CD6A0030**A6XXBD	31	775	23	578	18	451	335	152	45
45	W/F	CD6A0045**A6XXBD	31	775	23	578	18	451	381	173	45
50	W/F	CD6A0050**A6XXBD	31	775	23	578	18	451	396	180	45
75	W/F	CD6A0075**A6XXBD	37	940	28	705	22	552	596	270	50
112.5	F	CD6A0112**A6XXBD	37	940	28	705	22	552	734	333	50
150	F	CD6A0150**A6XXBD	46	1168	31	787	24	616	1092	495	50
225	F	CD6A0225**A6XXBD	53	1346	37	927	29	724	1635	742	55
300	F	CD6A0300**A6XXBD	53	1346	37	927	29	724	2176	987	55
450	F	CD6A0450**A6XXBD	Consult our Customer Service								
500	F	CD6A0500**A6XXBD	Consult our Customer Service								
600	F	CD6A0600**A6XXBD	Consult our Customer Service								
750	F	CD6A0750**A6XXBD	Consult our Customer Service								
1000	F	CD6A1000**A6XXBD	Consult our Customer Service								

(1) W = Wall mount F = Floor mount
(2) Catalog number

THREE-PHASE:

15 - 1000 kVA

2 x FCAN, 2 x FCBN 4 x 2.5%

STANDARD VOLTAGE

** (VH) 600 - 208Y/120 ** (VK) 600 - 240Y/139

** (VR) 600 - 480Y/277 ** (RH) 480 - 208Y/120

** (RK) 480 - 240Y/139

All weights and dimensions are approximate and subject to change without notice.
For the electrical schematic diagrams see Section 7, page 20