

## Eaton XT IEC contactor

### XTCE007B10A

#### Dimensions:

- **Height:** 2.67 IN
- **Length:** 2.95 IN
- **Width:** 1.77 IN

#### Weight:.5 LB

**Notes:**Screw terminals (6-65A); 5 mm (80-150A);  
no lugs (185-2000A)

**Warranties:** No Data

#### Specifications:

- **Amperage Rating:** 7A
- **Coil:** 110V 50 Hz, 120V 60 Hz
- **Coil Voltage:** 110 Vac 50 Hz, 120 Vac, 60 Hz
- **Contact Configuration:** 1NO
- **Frame Size:** 45 mm
- **Frequency Rating:** 50-60 Hz
- **Max Hp Rating:** 0.25, 0.75, 1/ 1.5, 2, 3, 5 hp  
(1/3PH @115,200,230/200,230,460,575 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing contactor

#### Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [XTCE\\_B 3D Model Xchange](#)
- [XTCE\\_B 2D PDF](#)
- [XTCE\\_B AutoCAD 2D Footprint](#)
- [XTCE\\_B 3D Inventor](#)
- [XTCE\\_B 2D Drawing Xchange](#)
- [Eaton Specification Sheet - XTCE007B10A](#)
- [Global Data Sheet - XTCE007B10A](#)

#### Certifications:

- UL Listed



- CSA Certified
- IEC 60947
- EN 60947

**Product compliance:**

- CE Marked
- RoHS Compliant

---

© 2016 Eaton. All rights reserved.