EarthTronics®

LED Floodlight
5750 Lumens, 50 Watt, Color Selectable

Specifications

ELECTRICAL

Watts: 50

Voltage: 100-277VAC

Power Factor: >0.9

Operating Temp. Range: -40°F to 131°F

LIGHT

Initial Lumens: 5750

Lumens per Watt: 115

Color Temperature: 4000K, 5000K

CRI: >80

AGENCY APPROVALS

cUL: Yes

UL: Yes

RoHS: Yes

DLC® Premium: Yes

PRODUCT DETAILS

Lens: Acrylic

Warranty: 5 years

Fixture Rated Life: 50,000 hours

APPLICATIONS

+ Comercial Building
+ Advertising Lighting
+ Landscape Lighting

EarthTronics®

Muskegon, Michigan 49441
T: 231.332.1188 | F: 231.726.5029
TOLL FREE: 866.632.7840
www.earthtronics.com

ORDER CODE:
11334

MODEL NUMBER:
FL50CCTBK1

UPC:
840791113349

**DLC® PRODUCT ID:**
PL190C5EAOJO

REBATE AVAILABILITY*

PRODUCT DESCRIPTION

The EarthTronics LED Floodlight provides security and general area illumination directed where required. Textured architectural bronze powder coat finish with tempered glass lens. This 30 watt floodlight operates at 114 lumens per watt efficiency and provides 3420 lumens. Switch between 4000K and 5000K easily at the time installation. Accepts 100 – 277 volt AC power supply. The long 50,000 hour is backed up with a 5 year warranty. DLC® Premium listed product.

PRODUCT FEATURES

+ 100-277VAC 50-60Hz
+ 50,000 hour rated life
+ 5 year warranty, 10 year limited
+ 2 color light selection 4000K & 5000K
+ Easy installation
+ Wide flood 150° beam angle (10%)
+ Ships standard with knuckle joint
+ Yoke mount is available
+ Photocell optional

8.50″
10.16″
2.12″

Please consult installation instructions for proper application and use of this fixture.
*Rebate availability access it here: www.earthtronics.com/rebate-finder

Rev. 3.13.20| ET11334