







Ty-Rap[®]





- I. WRAP CABLE TIE AROUND BUNDLE, TEXTURED RIB-SIDE IN.
- 2. THREAD TAIL OF CABLE TIE THROUGH HEAD UNTIL METAL LOCKING BARB FIRMLY ENGAGES.
 PULL TAIL THROUGH UNTIL HAND TIGHT.
- 3. FOR BEST RESULTS, COMPLETE INSTALLATION USING RECOMMENDED INSTALLATION TOOL. RECOMMENDED INSTALLATION TOOL(S): ERGI20 / WT-197 (MS90387-2)

REVISIONS	GENERAL NOTES	DESCRIPTION: TY-RAP CABLE TIE SELF-CLINCHING			
A SEE ECN (****)	I. ALL DIMENSIONS ARE FOR REFERENCE ONLY. 2. DIMENSIONS IN BRACKETS [] ARE IN METRIC UNITS.	(TY27M AND TY29M SERIES)			
FOR APPROVAL SIGNATURES & RELEASE DATE.		ORIGINAL PROJECT NO / (ECN NO)	SHEET NO:	REV. NO:	DRAWING NO:
PROJECT NO: ****		009M001527 / (000086131)	1 OF 2	A	WSD-003270

CATALOG	COLOR	MS NUMBERS
NO.	CODE	TYPE I CLASS I
TY27M	NATURAL	
TY27M-I	BROWN	MS3667-3-1
TY27M-2	RED	MS3667-3-2
TY27M-3	ORANGE	MS3667-3-3
TY27M-4	YELLOW	MS3667-3-4
TY27M-5	GREEN	MS3667-3-5
TY27M-6	BLUE	MS3667-3-6
TY27M-7	PURPLE	MS3667-3-7
TY27M-8	GRAY	MS3667-3-8
TY27M-9	MS NATURAL	MS3667-3-9
TY27M-10	WHITE	
TY27MX	UV BLACK	
TY27MX-0	MS BLACK	MS3667-3-0

CATALOG NO.	COLOR CODE	MS NUMBERS TYPE I CLASS I
TY29M	NATURAL	1112 1 02/100 1
TY29M-1	BROWN	MS3667-6-1
TY29M-2	RED	MS3667-6-2
TY29M-3	ORANGE	MS3667-6-3
TY29M-4	YELLOW	MS3667-6-4
TY29M-5	GREEN	MS3667-6-5
TY29M-6	BLUE	MS3667-6-6
TY29M-7	PURPLE	MS3667-6-7
TY29M-8	GRAY	MS3667-6-8
TY29M-9	MS NATURAL	MS3667-6-9
TY29M-10	WHITE	
TY29MX	UV BLACK	_
TY29MX-0	MS BLACK	MS3667-6-0

LENGTH "A": 30.0 [762] MAXIMUM BUNDLE DIA: 9.0 [229]

CATALOG NO.	COLOR	LENGTH "A" IN / mm	MAX. BUNDLE DIA. IN / mm	UL RECOGNIZED	UL LISTED
TY27M	NATURAL	13.4/340	4/102	YES	YES
TY27MX	BLACK	13.4/340	4/102	YES	YES
TY275M	NATURAL	18/457	5/127	YES	YES
TY275MX	BLACK	18/457	5/127	YES	YES
TY277M	NATURAL	24.3/617	7/177	YES	YES
TY277MX	BLACK	24.3/617	7/177	YES	YES
TY527M	NATURAL	13.4/340	4/102	YES	YES
TY527MX	BLACK	13.4/340	4/102	YES	YES
TY5275M	NATURAL	18/457	5/127	YES	YES
TY5275MX	BLACK	18/457	5/127	YES	YES
TY5277M	NATURAL	24.3/617	7/177	YES	YES
TY5277MX	BLACK	24.3/617	7/177	YES	YES
TY27IM	NATURAL	5.9/150	1/25	YES	YES
TY27IMX	BLACK	5.9/150	1/25	YES	YES

MATERIAL: NYLON 6/6 - CONFORMS TO ASTM D4066 PAIII MAX. CONTINUOUS USE TEMP: NATURAL/COLORS/MX-0:185°F/85°C MX:221°F/105°C

FLAMMABILITY RATING: UL94V-2 TENSILE STRENGTH: 120 LBS. [534N]

UL LISTED TYPE 2,21S

PLENUM RATED AH-2 (EXCEPT WEATHER RESISTANT NYLON) WEATHER RESISTANT NYLON: CONFORMS TO ASTM D4066 PA181

TY-RAP (SELF-CI	ABB		
ORIGINAL PROJECT NO / ECN NO	SHEET NO:	REV. NO:	DRAWING NO:
009M001527 / (000086131)	2 OF 2	Α	WSD -003270