

T2 TECHNOLOGY™ HACKSAW BLADES

T2 TECHNOLOGY™

A new blade design that delivers up to 100% longer blade life versus the prior generation of LENOX hacksaw blades

SHATTER RESISTANT

Bi-Metal construction allows blades to bend and flex without breaking



| TPI | LENGTH X WIDTH | | 1-PACK PROD NO | 2-PACK PROD NO | 10-PACK PROD NO | 100-PACK PROD NO | APPLICATION |
|-----|----------------|------------|-------------------|-------------------|--------------------|---------------------|----------------|
| | IN | MM | | | | | |
| 14 | 12 x 1/2 | 300 x 12.7 | — | — | 20143V214HE | — | Wood and Metal |
| 18 | 10 x 1/2 | 254 x 12.7 | — | 20163T018HE | 20140V018HE | — | Heavy Metal |
| 18 | 12 x 1/2 | 300 x 12.7 | 20154S218HE | 20160T218HE | 20144V218HE | 20116218HE | Heavy Metal |
| 24 | 10 x 1/2 | 254 x 12.7 | 20151S024HE | 23930T024HE | 20141V024HE | 20111024HE | Medium Metal |
| 24 | 12 x 1/2 | 300 x 12.7 | 20155S224HE | 20161T224HE | 20145V224HE | 20117224HE | Medium Metal |
| 32 | 10 x 1/2 | 254 x 12.7 | — | 20164T032HE | 20142V032HE | — | Thin Metal |
| 32 | 12 x 1/2 | 300 x 12.7 | 20156S232HE | 20162T232HE | 20146V232HE | 20118232HE | Thin Metal |

HT50 HIGH TENSION HACKSAW 50,000 PSI

HIGHEST TENSION. EVER

Unique I-Beam construction allows blade to tension up to 50,000 psi, resulting in fast, straight cuts

COMFORTABLE GRIPS

Rubberized handles allow for confident handling even in wet or cold environments

CONVERT TO A JAB SAW

Accepts any LENOX reciprocating saw blade to be used as a jab saw

CONVENIENT BLADE STORAGE

Store up to 5 extra 12" hacksaw blades in the I-Beam



| PROD NO | BLADE SPECIFICATION |
|-----------|---------------------------------|
| 12132HT50 | 12" (305mm) 24TPI Hacksaw Blade |



Tension



Use as a Jab Saw



Stores up to 5
Blades in I-Beam



Comfortable
Grips