



“Spitfire” Plastic Headbanded Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A STANDARDS



NP111

Combining lightweight and performance

- Dielectric
- Padded headband
- Adjustable height
- Lightweight
- Comfortable
- Good attenuation

NP111	Class A								NRR: 24 dB
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000
Mean Attenuation dB	16.7	20.0	31.4	38.4	36.3	37.5	37.6	37.0	35.1
Standard Deviation dB	2.8	2.7	3.0	3.2	2.5	3.6	3.2	2.9	1.9

“Spitfire” Plastic Cap-Mounted Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A STANDARDS



NP112

Combining lightweight and performance

- Dielectric
- Adjustable height
- Lightweight
- Comfortable
- Good attenuation
- Adjustable arm tension
- Parking position

NP112	Class A								NRR: 20 dB
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000
Mean Attenuation dB	15.8	17.3	23.2	30.6	33.9	35.9	36.9	38.5	38.6
Standard Deviation dB	3.0	2.6	3.6	3.5	3.4	4.0	3.0	3.8	3.8