

Model: NP120 Mirage Earmuff



Description:

NP120 Wire earmuff, neck-mounted, generally used in welding applications, offering a good adjustment setting and a low profile.

It is easy to adjust, and it offers a good attenuation performance for hearing protection.

Product Number	Description	Order Multiples	Case Quantity
NP120	Wire neck-mounted, Low profile, Very good attenuation	1	10

		CSA Standards / ANSI S3.19-1974 Regulations								
CSA Class	A	FREQUENCY IN HERTZ								
		125	250	500	1000	2000	3150	4000	6300	8000
MEAN ATTENUATION dB		15.3	19.6	27.9	36.3	35.9	40.5	42.2	41.9	41.5
STAND. DEVIATION dB		2.4	2.5	2.9	3.4	2.2	2.4	3.6	2.4	4.1
NRR	24 dB									

NRR	24 dB	COLOR	BLACK / YELLOW
TYPE	Wire Neck-Mounted Earmuff	COUNTRY OF ORIGIN	CANADA
CLASSIFICATION	None-Dielectric	CUP MATERIALS	ABS INSIDE FOAM: Acoustic foam
COMPLIANCE	ANSI S3.19-1974, CSA Z94.2-14	NECK-MOUNT BRACKET MATERIALS	Nylon – Chrome steel wires
CSA CLASSIFICATION	CLASS A	WEIGHT	211 g./ 7.4 oz.

REVISION: MAR- 2018

Head Office

2477, Michelin, Laval, Qc H7L 5B9
T: (450) 622-7374/ 1 877 446-3278
F: (450) 622-2243/ 1 877 463-2789

Fall Protection Manufacturing

175 Admiral Blvd., Mississauga, On L5T 2T3
T: (905) 565-9990
F: (905) 565-9906